BODY 930 BITUMEN UNDERBODY COATING



- Thixotropic material based on caoutchouc and tar
- Remains elastic and it is adhered perfectly
- Provides excellent underbody protection
- Dries quickly

Product Application:



It is applied on the underneath parts of the car. Applicable with a brush or a spray gun at a pressure of 5-6 bars.



Always mix well before use



Follow the application instructions mentioned in this TDS



Addition of 10-20% BODY EXTRA NITRO THINNER



Always wear protective equipment



Apply with spray gun Pressure 5-6 bar



Protect from humidity



Drying time 2-6h /22-25 °C



Always close tin after use

HB BODY SA AUTOMOTIVE REFINISHING INDUSTRY, GREECE

http://www.hbbody.com

Page 1of - 2

BODY 930 BITUMEN UNDERBODY COATING – Technical Data Sheet No 702

Flash Point:		
Solid Content (No thinner): 60% Weight VOC (2001/42/EC) The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 350g/L Cleaning of equipment: Clean after final use with Body 740 ACRYL NORMAL Body Extra Nitro Thinner Remarks: Allow for additional time for combi spray booths to reach the desired temperature Best results when used with HB BODY PRODUCTS It can be used by countries that do not adopt the VOC legislation as well.	Flash Point:	<0oC
The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 350g/L Cleaning of equipment: Clean after final use with Body 740 ACRYL NORMAL Body Extra Nitro Thinner Remarks: Allow for additional time for combi spray booths to reach the desired temperature Best results when used with HB BODY PRODUCTS It can be used by countries that do not adopt the VOC legislation as well.	Specific Gravity:	$1.07 \mathrm{g/cm^3}$
The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 350g/L Cleaning of equipment: Clean after final use with Body 740 ACRYL NORMAL Body Extra Nitro Thinner Remarks: Allow for additional time for combi spray booths to reach the desired temperature Best results when used with HB BODY PRODUCTS It can be used by countries that do not adopt the VOC legislation as well.	Solid Content (No thinner):	60% Weight
The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 350g/L Cleaning of equipment: Clean after final use with Body 740 ACRYL NORMAL Body Extra Nitro Thinner Remarks: Allow for additional time for combi spray booths to reach the desired temperature Best results when used with HB BODY PRODUCTS It can be used by countries that do not adopt the VOC legislation as well.	VOC (2001/42/EC)	2004/42/IIB(e)(840)350
the ready for use form of this product is 350g/L Clean after final use with Body 740 ACRYL NORMAL Body Extra Nitro Thinner • Allow for additional time for combi spray booths to reach the desired temperature • Best results when used with HB BODY PRODUCTS • It can be used by countries that do not adopt the VOC legislation as well.	The maximum VOC content in this	
Cleaning of equipment: Clean after final use with Body 740 ACRYL NORMAL Body Extra Nitro Thinner Remarks: • Allow for additional time for combi spray booths to reach the desired temperature • Best results when used with HB BODY PRODUCTS • It can be used by countries that do not adopt the VOC legislation as well.		
Clean after final use with Body 740 ACRYL NORMAL Body Extra Nitro Thinner Remarks: • Allow for additional time for combi spray booths to reach the desired temperature • Best results when used with HB BODY PRODUCTS • It can be used by countries that do not adopt the VOC legislation as well.	1 *	
Remarks: • Allow for additional time for combi spray booths to reach the desired temperature • Best results when used with HB BODY PRODUCTS • It can be used by countries that do not adopt the VOC legislation as well.		
 Remarks: Allow for additional time for combi spray booths to reach the desired temperature Best results when used with HB BODY PRODUCTS It can be used by countries that do not adopt the VOC legislation as well. 	Cleaning of equipment:	Clean after final use with Body 740 ACRYL NORMAL
desired temperature Best results when used with HB BODY PRODUCTS It can be used by countries that do not adopt the VOC legislation as well.		Body Extra Nitro Thinner
 desired temperature Best results when used with HB BODY PRODUCTS It can be used by countries that do not adopt the VOC legislation as well. 	Remarks:	• Allow for additional time for combi spray booths to reach the
 Best results when used with HB BODY PRODUCTS It can be used by countries that do not adopt the VOC legislation as well. 		desired temperature
It can be used by countries that do not adopt the VOC legislation as well.		<u>.</u>
legislation as well.		
±		• Store in a cool place. Guaranteed shelf life of 24 months in
unused original containers		unused original containers

This is a thixotropic material based on caoutchouc and tar. It is applied on the underneath parts of the car. It protects from rust, noise and it is highly resistant to road stone chipping. It remains elastic and it is adhered perfectly. It dries quickly and it cannot be painted because it contains asphalt. It can be applied with either a brush or a spray gun at 5-6 bar pressure

For professional use only. The information displayed on this sheet has been carefully selected though a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

Issue 1/2008, July 2008.