

**Контакт Palazzoli промишлен монофазен, противовлажен 32
А, 2P+E, 44 IP, син**



Ташев-Галвинг ООД
www.tashev-galving.com

MULTIMAX series

PRODUCT SPECIFICATIONS

Conformity to standards:	CEI EN 60309-1	IEC 60309-1
	CEI EN 60309-2	IEC 60309-2
	CEI EN 60529	IEC 60529
Protection rating:	IP44/IP67	Impact
resistance:	> IK 08	Glow
wire test:	850°C insert	Self-
extinguishing grade:	V2	Temperature
Operating:	-25°C - +50°C	

resistance:	Storage:	-30°C - +70°C	
Cable entry: stepped gland	16A 2P+	min: 8	max: 13 mm
	3P+	min: 8,5	max: 14 mm
	3P+N+	min: 10	max: 15,5 mm
	32A 2P+	min: 11,5	max: 17,5 mm
	3P+	min: 12,5	max: 19,5 mm
	3P+N+	min: 14	max: 21,5 mm
	63A 2P+	min: 17	max: 26 mm
	3P+	min: 19	max: 28,5 mm
	3P+N+	min: 21	max: 31,5 mm
Sezioni allacciabili dei conduttori	16A	min: 1	max: 2,5 mm ²
	32A	min: 2,5	max: 6 mm ²
	63A	min: 4	max: 10 mm ²



MULTIMAX SERIES
Protected straight connectors,
rapid wiring and low voltage
IP44

Rated current (A)	Frequency	Rated voltage	Voltage colour	Poles	h ref.	Palazzoli Code	Pack Q.ty
16	50-60Hz	110V	—	2P+	4	720124	5
	50-60Hz	110V	—	3P+	4	720134	5
	50-60Hz	110V	—	3P+N+	4	720144	5
	50-60Hz	230V	—	2P+	6	720126	10
	50-60Hz	230V	—	3P+	9	720139	5
	50-60Hz	230V	—	3P+N+	9	720149	5
	50-60Hz	400V	—	2P+	9	720129	5
	50-60Hz	400V	—	3P+	6	720136	10
32	50-60Hz	400V	—	3P+N+	6	720146	5
	50-60Hz	110V	—	2P+	4	720224	5
	50-60Hz	110V	—	3P+	4	720234	5
	50-60Hz	110V	—	3P+N+	4	720244	5
	50-60Hz	230V	—	2P+	6	720226	5
	50-60Hz	230V	—	3P+	9	720239	5
	50-60Hz	230V	—	3P+N+	9	720249	5
	50-60Hz	400V	—	2P+	9	720229	5
50-60Hz	400V	—	3P+	6	720236	5	
50-60Hz	400V	—	3P+N+	6	720246	5	

Characteristics:
all products are packed separately.
Complementary items:



MULTIMAX SERIES
Watertight straight connectors,
rapid wiring
low voltage
IP67

Rated current (A)	Frequency	Rated current	Voltage colour	Poles	h ref.	Palazzoli Code	Pack Q.ty
16	50-60Hz	110V	—	2P+	4	730124	10
	50-60Hz	230V	—	2P+	6	730126	10
	50-60Hz	400V	—	3P+	6	730136	10
	50-60Hz	400V	—	3P+N+	6	730146	10
32	50-60Hz	110V	—	2P+	4	730224	10
	50-60Hz	230V	—	2P+	6	730226	10
	50-60Hz	400V	—	3P+	6	730236	6
	50-60Hz	400V	—	3P+N+	6	730246	6

Uses:
suitable for general use, the speed and simplicity of wiring make them particularly ideal for series operations.
The colour of the cover and cable clamp indicates the electrical characteristics.
Complementary items:
plugs on page 16.
Notes:
special versions on page 28.



MULTIMAX SERIES
Watertight straight connectors
63A rapid wiring low voltage

IP67

Rated current (A)	Frequency	Rated voltage	Voltage colour	Poles	h ref.	Palazzoli Code	Pack Q.ty
63	50-60Hz	230V	—	2P+	6	730326	1
	50-60Hz	400V	—	3P+	6	730336	1
	50-60Hz	400V	—	3P+N+	6	730346	1

Uses:
suitable for general use, the speed and simplicity of wiring make them particularly ideal for series operations. The colour of the cover and cable clamp indicates the electrical characteristics.
Complementary items:
plugs on page 16.
Notes:
special versions on page 27.

Продукт: [Контакт Palazzoli промишлен монофазен, противовлажен 32 А, 2P+E, 44 IP, син](#)
Категория: [Електрически контакти](#)
Бранд: [Palazzoli](#)
Категория бранд: [Контакт Palazzoli](#)