



WELDING INVERTERS

Welding inverter WME m 176

WME m 176 is equipped with:

- Compact and portable inverter for MMA, TIG welding
- Durable and impact resistance design with OKC cable connectors
- Easy to operate - only current setting needed
- Fan cooling
- Welds most electrodes from \varnothing 1,6 - 4,0 mm
- Capable to work on generator power source
- Thermal protection
- Automatic arc force
- Full color packaging

TECHNICAL DATA

Order No.:	301602002
MAIN SUPPLY (V/Ph Hz)	230/1 \pm 15% 50/60
FUSE, SLOW (A)	16
SETTING RANGE (A)	20-160
MAX. OUTPUT AT 15% DUTY CYCLE (MMA) A/V	160/26,4
MAX. OUTPUT AT 60% DUTY CYCLE (MMA) A/V	92/23,7
MAX. OUTPUT AT 100% DUTY CYCLE (MMA) A/V	71/22,8
RATED OUTPUT VOLTAGE (V)	20,8-26,6
OPEN CIRCUIT VOLTAGE (V)	68
POWER FACTOR AT MAX. CURRENT	0,93
DIAMETER OF ELECTRODES (mm)	1,6-4,0
OKC	50
PROTECTION CLASS	IP21S
DIMENSIONS (LxBxH mm)	230x363x185
WEIGHT (kg)	6,0



STANDARD EQUIPMENT

- MMA welding cable kit 1,2m
- returne cable kit (16 mm²) 1,9m
- Mask
- Brush

