

Технически характеристики

Борщанга PG за метал ф 25-217 мм





ref.	description	RPM	pack.
214.00	hexagonal shank Ø 8 mm - pilot drill Ø 6 mm - to drill from 20 mm to 123 mm - complete with HSS drill Ø 6 mm - wrench - 5 mm HSS cutting tool with 5% cobalt	250	5
215.00	hexagonal shank Ø 12 mm - pilot drill Ø 10 mm - to drill from 25 mm to 217 mm - complete with HSS drill Ø 10 mm - wrench - 6 mm HSS cutting tool with 5% cobalt	250	5
216.00	hexagonal shank Ø 8 mm - pilot drill Ø 4 mm - to drill from 27 mm to 104 mm - complete with HSS drill Ø 5 mm - wrench - Ø 5 mm HSS cutting tool with 5% cobalt	250	5

REPLACEMENT HSS CUTTING TOOL				
ref.	description	pack.		
214.10	5 mm for ref. 214.00	5		
215.10	6 mm for ref. 215.00	5		
216.10	Ø 5 mm for ref. 216.00	5		

Продукт: <u>Борщанга PG за метал ф 27-104 мм</u> Категория: <u>Боркорони за строителни материали</u>

Бранд: <u>PG</u>

Категория бранд: <u>Борщанга PG</u>