



Product Features

tesa® 4934 is a double-sided tape. It consists of a fabric backing with a thick, tacky adhesive coating. The synthetic rubber adhesive is solvent free.

tesa® 4934 is a general purpose mounting tape.

tesa® 4934 is easily hand tearable.

Main Applications

Due to the flexible fabric backing and the high coating weight it is particularly suited for mounting on rough, fibrous surfaces, for example carpet laying.

Technical Data	
Backing material	cloth
Colour	white
Thickness of tape	200 µm
Type of adhesive	synthetic rubber
Elongation at break	20 %
Tensile strength	35 N/cm
Type of liner	glassine

Adhesion to	
Steel (initial)	14.5 N/cm
PE (initial)	8 N/cm
PP (initial)	16 N/cm
PVC (initial)	14 N/cm
Steel (after 14 days)	24 N/cm
PE (after 14 days)	8.5 N/cm
PP (after 14 days)	24.5 N/cm
PVC (after 14 days)	22.5 N/cm

Properties	
Temperature resistance short term	60 °C
Temperature resistance long term	40 °C
Tack	++
Humidity resistance	+
Static shear resistance at 23 °C	++
Static shear resistance at 40 °C	++
Static shear resistance at 70 °C	-
Fogging	++
Ageing resistance (UV)	0

Evaluation across relevant tesa assortment: ++ very good, + good, 0 medium, - low