



PREMAxx 38 l/min-12 V-DC

ABK-ZVPP-4 m

Item number: 23 711
EAN: 4103810237119
Discount group: D

technical data

connecting cable with battery
terminal clips, length (m): 3
connection container: G 2" male, drum adapter and M 64 x 4 male
Connection discharge side: G 1" male
Hydraulic data
Pump design: axial gear
Delivery rate at free outflow (l/min): 38
discharge height max. (m): 15
Suction height (m): 2,5
flow media: Fuel oil and diesel
Motor data
Voltage (V): 12 V DC
Power consumption (A): 14
Power (kW): 0,18
Thermal protection: selfresetting
Duty cycle (min): 30
Rotations at 0,5 bar counterpressure (rpm): 6950
Type of construction: IMB5
Protection class: IP 44
material of pump housing and pump: PA
dimensions of pump LWH (mm): 90 x 120 x 350
weight of motor and pump (kg): 2,5

specification

- For 200 up to 1000 l container
- Axial wheel pump with manual pump assembly (23 730)
- Illuminated on/off switch
- Motor with thermal protection switch, self-resetting
- siphon protection acc. to WHG (German government regulation for environmental care), continuously active
- discharge hose 4 m, DN 19, G 1" male, G 1" female (23 144)
- Polypropylene nozzle valve, ZVPP (23161)
- Suction hose, 1,6 m, with brass strainer (87 842)
- Drum adapter, PA, G 2" male und M 64 x 4 male (87 912)
- valuable sales package

notes

- The pump is lightweight and very quiet in operation.
- Resistant against small dirt particles in the liquid to be discharged
- The liquid level can be lifted to operation level by manual pumping
- Can be manually operated in case of electric power blackout

packaging

Dimensions LxWxH (mm): 400 x 400 x 220
Weight (kg): 5,31
Packing unit: 1.0