

UNOplus Ratchet Lever Hoist



Details

Further technical development turns the ratchet lever hoist into the successor of our proven UNO model. The versatile tool for lifting, pulling and securing of loads is characterised by its compact design and robust stamped steel construction.

Features

- Due to optimized gearing and improved bearings in the housing cover a minimum effort is required to operate the short hand lever.
- Steel hand wheel as standard.
- Automatic screw-and-disc type load brake with corrosion protected components.
- Standard free chaining device to quickly attach the load or to pull the chain through the hoist in both directions.
- Robust chain guide rollers eliminate fouling and jamming of chain on the load sheave.
- Sturdy bottom block with encapsulated bolt connections
- Alloyed steel link chain with zinc-plated resp. yellow chromated finish, in accordance with national and international standards and regulations.
- Drop forged suspension and load hooks are made from non-aging, high tensile steel and fitted with robust safety latches.
- Stainless steel load chains.

Technical Data

Description	UNOplus Ratchet Lever Hoist
Description	1,5t 1,5m HOL
number of chain falls	1
Chain dimensions (d x p Inch)	8
Chain dimensions (t x p Inch)	24
Lift per one full lever turn (mm)	22
Pull on hand chain at WLL daN	35
Capacity (kg)	1.500
Weight at standard lift (1,5 m) kg	12.5

Ташев-Галвинг ООД
www.tashev-galving.com