

# MASONRY SAW

## TME700★★★


Cutting depth up to 270 mm



Removable water tank for easier cleaning.



Sturdy, balanced transport hook for easy crane transport.



Precise mitre cutting thanks to mitre stop.

The TME700\*\*\* convinces through maximum stability and robustness. The precise stainless-steel saw table guide guarantees a clean cut. Construction-site suitable leading pulleys, forklift guides and a crane hook ensure trouble-free transport.

The anti-contamination positioning of the water pump reduces servicing requirements to a minimum and ensures permanent tool cooling. The intelligent blade guard construction enables quick and easy blade installation.

# System & Accessories

## Technical data

Saw blade	
Max. cutting depth	270 mm
Max. saw blade Ø	700 mm
Cutting length	600 mm
Saw blade speed	1380 rpm
Saw blade holder Ø	60 mm
Carrier Ø	11.5 mm
Reference circle Ø	120 mm

## Drive

Drive/motor	Electric
Output	5.5 kW
Standard voltage/frequency	400 V / 50 Hz
Engine cooling	Air cooling
Saw blade drive	Direct

## Design

Infinitely adjustable cutting depths
Angle cutting function (angle stop)
Mitre cutting function (optional mitre stop)
Transport hook and fork lift guides
Pull-out water tank
Electric water pump

## Dimensions & Weight

Length	1470 mm
Width	910 mm
Height	1350 mm
Weight	220 kg

## System & Accessories

Masonry saw TME700***	
10989600	Masonry saw TME700*** / 400 V
Accessories	
10978735	Mitre stop (Jolly table)