







## **PHARMA 20 - INDUSTRIAL THREE PHASE**



CHEMICAL-PHARMACEUTICAL











- ✓ Side channel blower motor , powerful and silent, totally maintenance free, suitable for continuous duty
- ✓ Integrated filter cleaning system
- ✓ Complete steel construction
- ✓ Extractable collection container with optional use of disposable bags
- ✓ Low noise level

- ✓ Compact and mobile
- ✓ High filtration efficiency
- ✓ Conceived for fine and hazardous dust suction
- ✓ Accessory kit as standard

SUCTION UNIT			
Voltage	V - Hz	230 - 50	
Power	kW	1,8	
Electrical protection	IP	55	
Max waterlift	mmH2O	2.300/1.800	
Max air flow	m³/h	250	
Suction inlet	mm	50	
Noise Jevel (EN ISO 3744)	dB(A)	67	
3%			

FILTER UNIT			
Filter Type		Cartridge	
Surface - Diameter	cm²-mm	30.000 - 360	
Material - Efficiency	IEC 60335-2-69	Polyester - M PTFE	
Air load on filter	m³/m²/h	83	
Cleaning system		Dustop	

COLLECTION UNIT		
Discharge system		Roll-out container
Capacity	lt.	33
VOLUME		
Dimensions	cm	52x69x147h
Weight	kg	72





### **SUCTION UNIT**

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.



#### **FILTER UNIT**

Jacem: by

A Tex CERTIFICATION

The detachable steel collection tank has a quick release system for the rapid disposal of the aucked material.





# **OPTIONALS**

- ✓ ABSOLUTE HEPA FILTER
- ANTISTATIC FILTER CLASS M
- STAINLESS STEEL CHAMBER
- STAINLESS STEEL TANK AND FILTER CHAMBER
- TOTAL STAINLESS STEEL CONSTRUCTION
- INTERNAL POLISHING FOR FILTER CHAMBER AND TANK