

Application of Langsol® Strong Cut for PE and Scratch resistant Lacquers

Manufacturer: LIPPERT-UNIPOL GMBH
Rudolf-Harbig-Weg 10
42781 Haan / Germany

Tel.: +49 (0) 2129 / 9307 - 0
Fax: +49 (0) 2129 / 9307 - 23

Description: **Langsol® Strong Cut 9070**

Product Description

Langsol® Strong Cut 9070 has been developed for grinding and correcting small defects on the lacquer.

The composition of the Langsol® Strong Cut is ideal to remove minor scratches, leaving a very uniform surface in preparation for finishing

The grinding compound Langsol® Strong Cut has been developed together with the products Cut – Complete – Finish and NanoPolish, whereby the combination to be applied depends on the type of surface and the quality of the lacquer.

The Langsol® Strong Cut 9070 can be used on dark and sensitive surfaces.

A further advantage of the Langsol® Complete 9025: minimal residue on the polished parts and minimal quantity required.

This product meets the highest technical standards. Waste water has not been found to contain any contamination.

Colour	white emulsion
Density at 20 °C	approx. 1,30 g / cm ³
pH - value (Concentrate)	7,0 +/- 1,0
Viscosity	10000 - 15000 cP

Dosage / Application

The use of a polishing emulsion facilitates high stock removal and an excellent gloss on all lacquers or lacquered surfaces, in particular light scratches and polish marks are removed. The Langsol® Strong Cut 9070 has been developed for use with standard manual polishing equipment. Please take care to use pads in the correct dimensions.

Storage Conditions

Ideally store at 15 - 25 °C. Temperatures < 4°C should be avoided, since this may cause problems in consistency and stability of the product, which in turn could impair results.