

## Application of Langsol® Finish for PE Lacquer

Manufacturer: LIPPERT-UNIPOL GMBH  
Rudolf-Harbig-Weg 10  
42781 Haan / Germany

Tel.: +49 (0) 2129 / 9307 - 0  
Fax: +49 (0) 2129 / 9307 - 23

Description: **Langsol® Finish 8029**

### Product Description

**Langsol® Finish 8029** has been developed for high gloss polishing and the removal of haze or small defects on the lacquer.

The composition of the Langsol® Finish 8029 is ideal to remove minor scratches and holograms leaving a highly polished, mark-free surface.

**A 2500 grain finish is removed entirely when PE Lacquers are applied.**

The Langsol® Finish 8029 can be used on dark and sensitive surfaces.

A further advantage of the Langsol® Finish 8029: minimal residue on the polished parts.

This product meets the highest technical standards. Waste water has not been found to contain any contamination.

<b>Colour</b>	grey emulsion
<b>Density at 20 °C</b>	approx. 1,00 g / cm <sup>3</sup>
<b>pH - value (Concentrate)</b>	7,0 +/- 1,0
<b>Viscosity</b>	10000 - 15000 cP

### Dosage / Application

The use of a polishing emulsion facilitates high stock removal and an excellent gloss on all lacquers or lacquered surfaces, in particular light scratches and polish marks are removed. The Langsol® Finish has been developed for use with standard manual polishing equipment. Please take care to use pads in the correct dimensions.

### Storage Conditions

Ideally store at 15 - 25 °C. Temperatures < 4°C should be avoided, since this may cause problems in consistency and stability of the product, which in turn could impair results.