

Injection TPU 60D polyurethane wheels, polyamide 6 centre, swivel top plate bracket type NL



Wheel description

Injection TPU 60D polyurethane tread; hardness 60 Shore D. Polyamide 6 centre.

Plain bearing bore or roller bearing bore

The plain bearing bore results from a hole in the material forming the centre of the wheel and contains the axle.

In the roller bearing bore, the bearing housing is obtained by moulding and contains cylindrical roller bearings with polyamide 6 cage.







Axle


Axle composed of ground steel bush with bolt according to UNI EN 24017 and nut according to UNI EN 24032.







Swivel top plate bracket type NL

Swivel top plate bracket type NL. The plate, the ball race ring and the fork are made of pressed steel zinc plated finish; swivel actions: double ball greased race with dust protection seal made of polyethylene. The king pin is integral with top plate and duly rivetted.



	80	30	107	100x85	80x60	9	39	120	0,62	604201
	100	30	128	100x85	80x60	9	37	170	0,74	604202
	125	35	156	100x85	80x60	9	39	220	0,91	604203
	150	35	182	100x85	80x60	9	37	220	1,08	604204
	150	45	194	140x110	105x80	11	56	300	1,83	604211
	200	50	240	140x110	105x80	11	56	300	2,23	604206



	80	30	107	100x85	80x60	9	39	120	0,63	604501
	100	30	128	100x85	80x60	9	37	170	0,75	604502
	125	35	156	100x85	80x60	9	39	220	0,92	604503
	150	35	182	100x85	80x60	9	37	220	1,11	604504
	150	45	194	140x110	105x80	11	56	300	1,98	604511
	200	50	240	140x110	105x80	11	56	300	2,27	604506