

Injection TPU 80A polyurethane wheels, thermoplastic centre, swivel top plate bracket type NL



Wheel description

Injection TPU 80A polyurethane tread; hardness 80 Shore A. Thermoplastic centre.

Plain bearing bore or roller bearing bore

The plain bearing bore results from a hole in the material forming the centre of the wheel and contains the axle.


In the roller bearing bore, the bearing housing is obtained by moulding and contains cylindrical roller bearings with polyamide 6 cage.

Axle


Axle composed of ground steel bush with bolt according to UNI EN 24017 and nut according to UNI EN 24032.

Swivel top plate bracket type NL

Swivel top plate bracket type NL. The plate, the ball race ring and the fork are made of pressed steel zinc plated finish; swivel actions: double ball greased race with dust protection seal made of polyethylene. The king pin is integral with top plate and duly rivetted.



	80	30	107	100x85	80x60	9	39	75	0,62	614201
	100	30	128	100x85	80x60	9	37	120	0,74	614202
	125	35	156	100x85	80x60	9	39	180	0,91	614203
	150	35	182	100x85	80x60	9	37	220	1,08	614204
	150	45	192	140x110	105x80	11	56	250	1,83	614211
	200	50	240	140x110	105x80	11	56	300	2,23	614206



	80	30	107	100x85	80x60	9	39	75	0,63	614501
	100	30	128	100x85	80x60	9	37	120	0,75	614502
	125	35	156	100x85	80x60	9	39	180	0,92	614503
	150	35	182	100x85	80x60	9	37	220	1,11	614504
	150	45	192	140x110	105x80	11	56	250	1,98	614511
	200	50	240	140x110	105x80	11	56	300	2,27	614506