

**Injection TPU 60D polyurethane wheels, polyamide 6 centre, swivel top plate bracket type NL with front lock**



**Wheel description**

Injection TPU 60D polyurethane tread; hardness 60 Shore D.  
Polyamide 6 centre.

**Plain bearing bore or roller bearing bore**

The plain bearing bore results from a hole in the material forming the centre of the wheel and contains the axle.


In the roller bearing bore, the bearing housing is obtained by moulding and contains cylindrical roller bearings with polyamide 6 cage.







**Axle**


Axle composed of ground steel bush with bolt according to UNI EN 24017 and nut according to UNI EN 24032.







**Swivel top plate bracket type NL with front lock**

Swivel top plate bracket type NL. The plate, the ball race ring and the fork are of pressed steel zinc plated finish; swivel actions: double ball greased race with dust protection seal made of polyethylene. The king pin is integral with top plate and duly rivetted. The front brake is necessary to lock wheel and top plate rotation.



	80	30	107	100x85	80x60	9	39	120	120	0,81	606601
	100	30	128	100x85	80x60	9	37	120	170	0,89	606602
	125	35	156	100x85	80x60	9	39	120	220	1,05	606603
	150	35	182	100x85	80x60	9	37	120	220	1,21	606604
	150	45	194	140x110	105x80	11	56	156	300	2,11	606611
	200	50	240	140x110	105x80	11	56	156	300	2,49	606606



	80	30	107	100x85	80x60	9	39	120	120	0,84	606621
	100	30	128	100x85	80x60	9	37	120	170	0,90	606622
	125	35	156	100x85	80x60	9	39	120	220	1,07	606623
	150	35	182	100x85	80x60	9	37	120	220	1,23	606624
	150	45	194	140x110	105x80	11	56	156	300	2,16	606631
	200	50	240	140x110	105x80	11	56	156	300	2,16	606626