

Injection TPU 80A polyurethane wheels, thermoplastic centre, fixed bracket type NL



Wheel description

Wheel description
Injection TPU 80A polyurethane tread; hardness 80 Shore A.
Thermoplastic centre.

Plain bearing bore or roller bearing bore

Plain bearing bore or roller bearing bore
The plain bearing bore results from a hole in the material forming the centre of the wheel and contains the axle.

In the roller bearing bore, the bearing housing is obtained by moulding and contains cylindrical roller bearings with polyamide 6 cage.

Axle

AXLE
Axle composed of ground steel bush with bolt according to UNI EN 24017 and nut according to UNI EN 24032.

Fixed bracket type NL

Fixed bracket type NL
Fixed bracket type NL. The fork is made of pressed steel zinc plated.

										
	80	30	107	100x85	80x60	9	75	0,38	615701	
	100	30	128	100x85	80x60	9	120	0,43	615702	
	125	35	156	100x85	80x60	9	180	0,66	615703	
	150	35	182	100x85	80x60	9	220	0,80	615704	
	150	45	192	140x110	105x80	11	250	1,46	615711	
	200	50	240	140x110	105x80	11	300	1,81	615706	

										
	80	30	107	100x85	80x60	9	75	0,41	615901	
	100	30	128	100x85	80x60	9	120	0,43	615902	
	125	35	156	100x85	80x60	9	180	0,67	615903	
	150	35	182	100x85	80x60	9	220	0,82	615904	
	150	45	192	140x110	105x80	11	250	1,51	615911	
	200	50	240	140x110	105x80	11	300	1,86	615906	