



Wall mounting water heaters with heat exchanger		72270T	72270HT	72266T	72266HT
CHARACTERISTICS		Enameled	Stainless	Enameled	Stainless
Rated volume	L	100		120	
Rated voltage	V	220-230~			
Rated electrical power	kW	3			
Rated pressure	bar	6			
Maximum D.H.W. tank temperature in	°C	75			
Heat exchange surface area	m ²	0,41	0,56	0,53	0,66
Heat exchange power	kW	-	-	12,8	-
Heat exchange inside volume	L	2	4,4	2,58	5,24
Weight when empty	kg	40	31	47	35
CONNECTIONS					
1: Heating coil - Feed	"GAS/F	3/4			
2: Heating coil - Return	"GAS/F	3/4			
3: Hot water outlet	"GAS/M	1/2			
4: Fresh water inlet (Drain) Safety valve	"GAS/M	1/2			
5: Temperature indicator	-	-			
6: Control panel	-	-			
DIMENSIONS					
Level A	mm	181		262	
Level B	mm	385		450	
Level D	mm	Ø460			
Level F	mm	912		1079	
Level I	mm	474			
Level J	mm	93			
Level K	mm	100			
Level L	mm	974		1141	
Level M	mm	240			
Level N	mm	171			
Level P	mm	32			