



Pos. Nr. Rep.	Stück/ Gerät Qty./ Unit Qté./ Unité	Bestellbezeichnung	Bestell-Nr. / Part No. / Référence				Description
			F 430 S -41/38	F 430 S -41/37Z	F 430 S -50/38	F 430 S -50/45Z	
	1	Innenrohr kpl., Pos. 1-4,6-14,19,20 Eintauchtiefe 700 mm Eintauchtiefe 1000 mm Eintauchtiefe 1200 mm	430 90 259 430 90 260 430 90 261	430 90 269 430 90 270 430 90 271	430 90 259 430 90 260 430 90 261	430 90 279 430 90 280 430 90 281	Inner tube cpl., Pos. 1-4,6-14,19,20 Immersion length 700 mm Immersion length 1000 mm Immersion length 1200 mm
	1	Außenrohr kpl., Pos. 5,15-18,21,22 Eintauchtiefe 700 mm Eintauchtiefe 1000 mm Eintauchtiefe 1200 mm	430 90 312 430 90 313 430 90 314	430 90 322 430 90 323 430 90 324	430 90 340 430 90 341 430 90 342	430 90 332 430 90 333 430 90 334	Outer tube cpl., Pos. 5,15-18,21,22 Immersion length 700 mm Immersion length 1000 mm Immersion length 1200 mm
	1 1 2 3	1 1 1 1	Kupplungskäfig kpl., Pos 1-3 Kupplungsstern Kupplungskäfig Rillenkugellager	425 22 000 410 14 028 420 51 275 922 40 005	425 22 000 410 14 028 420 51 275 922 40 005	425 22 000 410 14 028 420 51 275 922 40 005	425 22 000 410 14 028 420 51 275 922 40 005
4	1	O-Ring Ø 32,2 x 3 (FKM)	925 65 003	925 65 003	925 65 003	-	O-ring Ø 32,2 x 3 (FKM)
	1	O-Ring Ø 32,2 x 3 (FEP)*	925 65 020	925 65 020	925 65 020	-	O-ring Ø 32,2 x 3 (FEP)*
4	1	O-Ring Ø 41 x 3 (FKM)	-	-	-	925 75 022	O-ring Ø 41 x 3 (FKM)
	1	O-Ring Ø 41 x 3 (FEP)*	-	-	-	925 75 038	O-ring Ø 41 x 3 (FEP)*
5	1	Außenrohr Eintauchtiefe 700 mm Eintauchtiefe 1000 mm Eintauchtiefe 1200 mm	430 21 107 430 21 110 430 21 112	430 21 107 430 21 110 430 21 112	430 21 307 430 21 310 430 21 312	430 21 207 430 21 210 430 21 212	Outer tube Immersion length 700 mm Immersion length 1000 mm Immersion length 1200 mm
6	1 1	Innenrohr mit Pos. 7, 10 und 11 Eintauchtiefe 700 mm Eintauchtiefe 1000 mm Eintauchtiefe 1200 mm	430 90 292 430 90 293 430 90 294	430 90 292 430 90 293 430 90 294	430 90 292 430 90 293 430 90 294	430 90 302 430 90 303 430 90 304	Inner tube with Pos. 7, 10 and 11 Immersion length 700 mm Immersion length 1000 mm Immersion length 1200 mm
7	3 5 6	Stützlager mit Pos. 8 Eintauchtiefe 700 mm Eintauchtiefe 1000 mm Eintauchtiefe 1200 mm	920 51 012	920 51 012	920 51 012	920 51 012	Support bearing with Pos. 8 Immersion length 700 mm Immersion length 1000 mm Immersion length 1200 mm
8	1	O-Ring Ø 10 x 2 (NBR)	925 23 005	925 23 005	925 23 005	925 23 005	O-ring Ø 10 x 2 (NBR)
9	1	Welle Eintauchtiefe 700 mm Eintauchtiefe 1000 mm Eintauchtiefe 1200 mm	420 51 247 420 51 250 420 51 252	420 51 247 420 51 250 420 51 252	420 51 247 420 51 250 420 51 252	420 51 247 420 51 250 420 51 252	Shaft Immersion length 700 mm Immersion length 1000 mm Immersion length 1200 mm
10	2	Gleitlager	920 51 013	920 51 013	920 51 013	920 51 013	Slide bearing
11	1	Zentrierstern	420 51 282	420 51 282	420 51 282	430 21 201	Centering star
12	1	Wellendichtring (FKM)	925 11 001	925 11 001	925 11 001	925 11 001	Shaft seal (FPM)
13	1	Gleitringdichtung (FKM)	958 25 055	958 25 055	958 25 055	958 25 055	Sliding ring gasket (FKM)
	1	Gleitringdichtung (FFKM)*	958 25 092	958 25 092	958 25 092	958 25 092	Sliding ring gasket (FFKM)*
14	1	Rotor	420 24 296	430 21 431	420 24 296	430 21 401	Impellor
15	1	Druckring	-	430 21 400	-	-	Pressure ring
16	1	Potentialausgleich (Anschlussteile)	947 12 011	947 12 011	947 12 011	947 12 011	Earth connection (connecting parts)
19	1	Gleitlager	920 51 013	920 51 013	920 51 013	920 51 013	Slide bearing
20	1	Wellendichtring (NBR)	925 10 001	925 10 001	925 10 001	925 10 001	Shaft seal (NBR)
21	1	Sicherungsring	918 80 002	918 80 002	918 80 002	918 80 002	Circlip
22	1	Überwurfmutter	907 90 070	907 90 070	907 90 070	907 90 070	Union nut
	1	Überwurfmutter(CuZn)*	907 90 001	907 90 001	907 90 001	907 90 001	Union nut (brass)*
		Lebensmittel-Schmierfett / kg (für Wellendichtringe und Innenrohr)	952 00 012	952 00 012	952 00 012	952 00 012	Food grade grease / kg (for shaft seals and inner tube)
		Zubehör: wahlweise:					Accessories: optional:
23	1	Schlauchanschluss DN 19, Pos. 23-25	959 04 061	959 04 061	959 04 061	959 04 061	Hose connection DN 19, Pos. 23-25
24	1	Knebelüberwurfmutter G 1 1/4	907 90 002	907 90 002	907 90 002	907 90 002	Union nut G 1 1/4
25	1	Flachdichtung	925 64 002	925 64 002	925 64 002	925 64 002	Flat seal
	1	Schlauchstecker DN 19	959 05 093	959 05 093	959 05 093	959 05 093	Hose connector DN 19
		wahlweise:					optional:
23	1	Schlauchanschluss DN 25, Pos. 23-25	959 04 041	959 04 041	959 04 041	959 04 041	Hose connection DN 25, Pos. 23-25
24	1	Knebelüberwurfmutter G 1 1/4	907 90 002	907 90 002	907 90 002	907 90 002	Union nut G 1 1/4
25	1	Flachdichtung	925 64 002	925 64 002	925 64 002	925 64 002	Flat seal
	1	Schlauchstecker DN 25	959 05 048	959 05 048	959 05 048	959 05 048	Hose connector DN 25
26	1	FLUX-Clip * als Sonderausführung lieferbar	001 10 424	001 10 424	001 10 424	001 10 424	FLUX-Clip * available as special version
Rights reserved to make alterations and / or modifications							