

WE 24-230 MVT (606469000) Angle Grinder

(220-240 V / 50 - 60 Hz); Cardboard box

Order no. 606469000 EAN 4007430268204



Product may differ from Image













- Metabo safety switch prevents unintentional start
- Starting current limitation prevents the actuation of the lock on start-up
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly for high user protection
- Electronic overload protection and restart protection
- LED signal indicates triggered restart protection or overheating
- Tool-free adjustable guard; twist-proof
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health
- Side handle can be mounted in three positions
- Rotating main handle: high safety and better handling when cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1 / 2



Technical data	
Characteristics	
Grinding wheel Ø	230 mm / 9 "
Rated input power	2400 W
Output power	1600 W
No-load speed	6600 /min
Revolutions at rated load	4600 /min
Torque	17 Nm / 150 in-lbs
Spindle thread	M 14
Weight (without power cable)	5.8 kg / 12.8 lbs
Cable length	4 m / 13 ft
Vibration	
Surface grinding	4.8 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Grinding with sandpaper	2.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Noise emission	
Sound pressure level	94 dB(A)
Sound power level (LwA)	105 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Guard

Metabo VibraTech (MVT) side handle

Flat-pin spanner

Inner support flange

Nut with two holes

www.metabo.com 2 / 2