

Шило Husqvarna Construction за хидравличен къртач 65x630 мм, цилиндрична опашка





MULTI GRAPPLER	MG 200	MG 100
TECHNICAL SPECIFICATIONS		
Weight, kg	□□□	□□ Max
jaw opening, mm	□□□	□□□
Force, kN/t	□□/□□	
Width, mm	□□□	□□□
RECOMMENDED FOR		
	DXR □□□/□□□/□□□	DXR □□□
ARTICLE INFORMATION		
	□□□ □□□-□□, incl. hoses and adapter plate	□□□ □□□-□□, incl. hoses and adapter plate



TECHNICAL SPECIFICATIONS			
Weight, kg	□□□	□□□	□□□
RECOMMENDED FOR			
	DXR □□□	DXR □□□/□□□/□□□	DXR □□□
ARTICLE INFORMATION			
	□□□ □□□□-□□, incl. hoses and adapter plate	□□□ □□□□-□□, incl. hoses and adapter plate	□□□ □□□□-□□, incl. hoses and adapter plate



Chisel cross	Chisel wide	Chisel moil point	Bushing Pad
ACCESSORIES 98 302			
Heat protection kit, breaker □□□ □□			
□□-□□ Chisel cross, □□ cm			□□□
□□ □□-□□ Chisel wide, □□ cm			□□□
□□ □□-□□ Chisel moil point, □□ cm			□□□
Chisel moil point			
□□ □□-□□ Bushing Pad			□□□
□□ □□-□□ Dust reduction kit, breaker			□□□ □□
□□ □□-□□			□□□ □□
Heat protection kit, breaker □□□ □□			
□□-□□ Chisel cross, □□ cm			□□□
□□ □□-□□ Chisel wide, □□ cm			□□□
Chisel cross			
□□ □□-□□ Chisel X-profile, long, □□ cm			□□□
□□ □□-□□ Bushing Pad			□□□
□□ □□-□□ Dust reduction kit, breaker			□□□
□□ □□-□□			□□□ □□



DRUM CUTTER	DC 300
TECHNICAL SPECIFICATIONS	
Service weight, kg	
<input type="checkbox"/> Total width cutting head, mm	□□
<input type="checkbox"/> Diameter of cutter drum, mm	□□
<input type="checkbox"/> Number of picks, pcs	□□
Maximum cutting force @ □□□ bar, kN	□□□
Maximum torque @ □□□ bar, kNm	□.□
Maximum rock hardness, MPA	□□
RECOMMENDED FOR	
DXR □□□/□□□/□□□	
ARTICLE INFORMATION	
□□□ □□□□-□□, incl. hoses and adapter plate	

Chisel cross, □□ cm

□□□ □□

□□
-□

Продукт: [Шило Husqvarna Construction за хидравличен къртач 65x630 мм, цилиндрична опашка](#)
 Категория: [Консумативи за къртачи и перфоратори](#)
 Бранд: [Husqvarna Construction](#)
 Категория бранд: [Шило Husqvarna Construction](#)