



# PORTABLE ELECTRIC DINGO



The Dingo single-phase, portable, electronic vibrator from ENAR which is protected by its robust design and thanks to its eternal housing which surrounds the motor. It has been designed to transmit power through a transmission which turns, causing an eccentric inside the poker head to spin at 12,000rpm and generate vibration.

Designed & Manufactured in Europe to a high standard of quality. Manufactured using high quality materials ensures high resistance. The Dingo uses an oversized motor and double insulation to guarantee its performance in every job condition.



## + Robust & Resistant

Against Damage.

The Dingo from Enar uses 3 handles to protect the motor and housing against damage. On top of this, the housing itself is made from high quality materials for any unlikely scenario where the handles need additional help protecting the motor.



## + Secure

In any given situation.


The motor from the Dingo is has been double insulated and also has an oversized motor to guarantee a high performance in all working conditions.



## + Manageability

Whatever the job or testing situation may be.

Thanks to the 3 handles that surround the motor and housing, the Dingo is far more comfortable to hold regardless of the length of transmission/drive, unlike other concrete vibrators.



## + Ease of Use

In any given situation.

The switch for the DINGO is at the back of the housing, behind a handle. This means the switch is protected as well as also being watertight. It also provides the advantage that you can use long or short transmissions and the switch will be close to your hand unlike other models.

## TECHNICAL DATA

| MODEL      | WEIGHT (Kg) | VOLTAGE (V) | FREQUENCY (Hz) | POWER (W) | DIMENSIONS (LxWxH) |
|------------|-------------|-------------|----------------|-----------|--------------------|
| DINGO 230V | 5.8         | 230 1~      | 50-60          | 2,300 W   | 354x244x229        |
| DINGO 115V | 5.8         | 115 1~      | 50-60          | 2,300 W   | 354x244x229        |

- › High resistant housing, also protected against dust and rain (IP44)
- › Oversized motor and double insulation.
- › Other couplings available upon request.
- › Includes a shoulder strap.

## AX HEADS

| MODEL | DIAMETER (mm) | LENGTH (mm) | WEIGHT (Kg) | SPEED (r.p.m) | PERFORMANCE m³/h |
|-------|---------------|-------------|-------------|---------------|------------------|
| AX 25 | 25            | 285         | 0.8         | 14,000        | 10               |
| AX 32 | 32            | 366         | 1.7         | 13,750        | 14               |
| AX 40 | 40            | 335         | 2.2         | 13,500        | 17               |
| AX 48 | 48            | 335         | 3.2         | 12,500        | 28               |
| AX 58 | 58            | 344         | 4.5         | 12,000        | 35               |

- › Oversized eccentric.
- › Easily interchanged poker heads.
- › 4 oil lubricated bearings with double lock.

## FLEXIBLE TRANSMISSIONS

| MODEL              | LENGTH (m) | WEIGHT (Kg) |
|--------------------|------------|-------------|
| TDX 0,6 - TDXE 0,6 | 0.6        | 2.6         |
| TDX 1 - TDXE 1     | 1          | 3           |
| TDX 1,5 - TDXE 1,5 | 1.5        | 3.5         |
| TDX 2 - TDXE 2     | 2          | 4           |
| TDX 3 - TDXE 3     | 3          | 5           |
| TDX 4 - TDXE 4     | 4          | 6           |
| TDX 5 - TDXE 5     | 5          | 7           |
| TDX 6 - TDXE 6     | 6          | 8           |

- › Reinforced TDX transmission/Drive.
- › The TDXE is only for poker sizes AX25 and AX32.
- › Vulcanized transmission at the poker end, providing protection to the part of the transmission most likely to wear out or break.

