

# PREMIUM★★★ WET DRILLING BITS

## CDL★★★ | IN TGD®-TECHNOLOGY

### (FROM Ø 47 mm)

+ **Consistently very fast cutting performance and noticeable smooth running** with TGD® Technology (Tyrolit Grain Distribution), a unique technology developed by Tyrolit for the optimised distribution of grain.

+ **Very long lifetime.**




Drill motors up to 3 kW | soft to medium-hard concrete aggregates. Quality tools for the most demanding applications and maximum economic

efficiency. Excellent and consistent performance, universal use and smooth core removal. Segmented drill from Ø 47 mm with TGD® Tech-

nology and new segment height of 11.3 mm. Laser welded segments up to a Ø 250 mm for maximum safety.

**PREMIUM★★★ WET DRILLING BITS**  
CDL★★★ | in TGD®-Technology (from Ø 47 mm)



	Type no.	Dimension	Segment height
	HOHL3		
	854317	14x400xR1/2"	7
	474990	15x400xR1/2"	7
	474991	16x400xR1/2"	7
	474993	18x400xR1/2"	7
	474995	20x400xR1/2"	7
	474997	22x400xR1/2"	7
	475000	24x400xR1/2"	7
	475009	25x400xR1/2"	7
	475010	28x400xR1/2"	7
	475011	30x400xR1/2"	7
	475012	32x400xR1/2"	7
	475014	37x450xR1/2"	7
	475015	40x450xR1/2"	7
	475016	42x450xR1/2"	7