

Длето Husqvarna Construction за хидравличен къртач 630х65 мм, цилиндрична опашка



Ташев-Галвинг ООД
www.tashev-galving.com



MULTI GRAPPLER	MG 200	MG 100
TECHNICAL SPECIFICATIONS		
Weight, kg	□□□	□□ Max
jaw opening, mm	□□□	□□□
Force, kN/t	□□/□□	□□□
Width, mm	□□□	□□□
RECOMMENDED FOR		
	DXR □□□/□ □□/□□□	DXR □□□
ARTICLE INFORMATION		
	□□□ □□ □□-□□, incl. hoses and adapter plate	□□□ □□ □□-□□, incl. hoses and adapter plate



TECHNICAL SPECIFICATIONS			
Weight, kg	□□□	□□□	□□□
RECOMMENDED FOR			
	DXR □□□	DXR □□□/□□□/□□□	DXR □□□
ARTICLE INFORMATION			
	□□□ □□□□-□□, incl. hoses and adapter plate	□□□ □□□□-□□, incl. hoses and adapter plate	□□□ □□□□-□□, incl. hoses and adapter plate



Chisel cross	Chisel wide	Chisel moil point	Bushing Pad	
ACCESSORIES SB 302				
Heat protection kit, breaker				□□ □□
□□-□□ Chisel cross, □□ cm				□□ □□
□□ □□-□□ Chisel wide, □□ cm				□□ □□
□□ □□-□□ Chisel moil point, □□ cm				□□ □□
□□ □□-□□ Chisel moil point, long, □□ cm				□□ □□
□□ □□-□□ Bushing Pad				□□ □□
□□ □□-□□ Dust reduction kit, breaker				□□ □□
□□ □□-□□				
Heat protection kit, breaker				□□ □□
□□-□□ Chisel cross, □□ cm				□□ □□
□□ □□-□□ Chisel wide, □□ cm				□□ □□
□□ □□-□□ Chisel moil point, □□ cm				□□ □□
□□ □□-□□ Chisel X-profile, long, □□ cm				□□ □□
□□ □□-□□ Bushing Pad				□□ □□
□□ □□-□□ Dust reduction kit, breaker				□□ □□
□□ □□-□□				□□ □□



DRUM CUTTER		DC 200
TECHNICAL SPECIFICATIONS		
Service weight, kg		
		□□
□ Total width cutting head, mm		
		□□
□ Diameter of cutter drum, mm		
		□□
□ Number of picks, pcs		□□
Maximum cutting force @ □□□ bar, kN		□□□
Maximum torque @ □□□ bar, kNm		□.□
Maximum rock hardness, MPA		□□
RECOMMENDED FOR		
DXR □□□ / □□□ / □□□ / □□□		
ARTICLE INFORMATION		
□□□ □□ □□-□□, incl. hoses and adapter plate		

Chisel cross, □□ cm

□□□ □□

□□
-□

Продукт: [Длето Husqvarna Construction за хидравличен къртач 630x65 мм, цилиндрична опашка](#)
 Категория: [Консумативи за къртачи и перфоратори](#)
 Бранд: [Husqvarna Construction](#)
 Категория бранд: [Длето Husqvarna Construction](#)