

Cordless Rotary Hammer with SDS plus

GBH 18V-28 D



BOSCH

Invented for life



With outstanding force: 18V D-handle rotary hammer with KickBack Control

The most important data

Battery voltage	18.0 V
Drilling dia. in concrete with hammer drill bits	4 – 28 mm
Impact rate at rated speed	0 – 4,250 bpm

Part Number 0 611 919 003

Technical data

Technical data

Impact rate at rated speed	0 – 4,250 bpm
Rated speed	0 – 950 rpm
Battery voltage	18.0 V
Weight excl. battery	3 kg
Tool holder	SDS plus
Packaging dimensions (width x length x height)	245 x 475 x 109 mm
BITURBO	No

Drilling range

Drilling dia. in concrete with hammer drill bits	4 – 28 mm
Opt. app. range in concrete with hammer drill bits	8 – 16 mm

Noise/vibration information

Hammer drilling in concrete

Vibration emission value ah	10.1 m/s ²
Uncertainty K	1.5 m/s ²

Drilling in metal

Vibration emission value ah	2.5 m/s ²
Uncertainty K	1.5 m/s ²

Screwdriving

Vibration emission value ah	2.5 m/s ²
Uncertainty K	1.5 m/s ²

Chiselling in concrete

Vibration emission value ah	7.2 m/s ²
Uncertainty K	1.5 m/s ²

Advantages:

- Powerful cordless performance, stronger than cored GBH 2-28; brushless motor delivers 3.4 J of impact energy, power-to-weight ratio of 1.1 J/kg
- Compatible to the additional and extremely lightweight dust extractor GDE 28 D with filter cleaning mechanism for dustless drilling
- KickBack Control, which minimises hand and arm injuries by instantly shutting down the rotary hammer and Vibration Control for increased user protection

