

HIKOKI

Cordless Driver Drill

36V DS 36DC

MV RFC
MULTI VOLT
REACTIVE FORCE CONTROL
BRUSHLESS



Cordless Impact Driver Drill

36V DV 36DC

MV RFC
MULTI VOLT
REACTIVE FORCE CONTROL
BRUSHLESS



Cordless Driver Drill

18V DS 18DC

RFC
REACTIVE FORCE CONTROL
BRUSHLESS



Cordless Impact Driver Drill

18V DV 18DC

RFC
REACTIVE FORCE CONTROL
BRUSHLESS



Specifications

Model	DS 36DC	DV 36DC	DS 18DC	DV 18DC
Battery Voltage	36V		18V	
Drill Chuck	1.5 - 13mm Keyless			
Capacity	Brick	-	22mm	20mm
	Mild Steel	20mm		16mm
	Soft Wood	118mm		102mm
	Wood Screw (D x L)	16 x 100mm		12 x 100mm
Machine Screw	6mm			
Max Torque*1	Hard : 155Nm Soft : 100Nm		Hard : 140Nm Soft : 70Nm	
No Load Speed	High : 0 - 2,200/min Low : 0 - 550/min		High : 0 - 2,000/min Low : 0 - 500/min	
Impact Rate	-	0 - 33,000/min	-	0 - 30,000/min
Overall Head Length	190mm			
Weight*2	2.8kg (with BSL36A18) 3.1kg (with BSL36B18)*3		2.6kg (with BSL1840M) 2.8kg (with BSL36A18 / BSL1850MA) 3.1kg (with BSL36B18)*3	
Standard Accessories*4	2 Batteries (BSL36A18), Charger (UC18YSL3), Driver Bit, Side Handle, Hook, Battery Cover, Carrying Case		2 Batteries (BSL36A18 / BSL1850MA / BSL1840M), Charger (UC18YSL3 / UC18YFSL), Driver Bit, Side Handle, Hook, Battery Cover, Carrying Case	

*1. With the BSL36A18 battery.

*2. Weight according to EPTA-Procedure 01/2014.

*3. Sold separately.

*4. Standard accessories vary by country or area.