

## HIKOKI

### Cordless Driver Drill

**36V DS 36DC**

**MV RFC**  
MULTI VOLT  
REACTIVE FORCE CONTROL  
**BRUSHLESS**



### Cordless Impact Driver Drill

**36V DV 36DC**

**MV RFC**  
MULTI VOLT  
REACTIVE FORCE CONTROL  
**BRUSHLESS**



### Cordless Driver Drill

**18V DS 18DC**

**RFC**  
REACTIVE FORCE CONTROL  
**BRUSHLESS**



### Cordless Impact Driver Drill

**18V DV 18DC**

**RFC**  
REACTIVE FORCE CONTROL  
**BRUSHLESS**



### Specifications

Model	DS 36DC	DV 36DC	DS 18DC	DV 18DC
Battery Voltage	36V		18V	
Drill Chuck	1.5 - 13mm Keyless			
Capacity	Brick	-	22mm	20mm
	Mild Steel	20mm		16mm
	Soft Wood	118mm		102mm
	Wood Screw (D x L)	16 x 100mm		12 x 100mm
	Machine Screw	6mm		
Max Torque*1	Hard : 155Nm Soft : 100Nm		Hard : 140Nm Soft : 70Nm	
No Load Speed	High : 0 - 2,200/min Low : 0 - 550/min		High : 0 - 2,000/min Low : 0 - 500/min	
Impact Rate	-	0 - 33,000/min	-	0 - 30,000/min
Overall Head Length	190mm			
Weight*2	2.8kg (with BSL36A18) 3.1kg (with BSL36B18)*3		2.6kg (with BSL1840M) 2.8kg (with BSL36A18 / BSL1850MA) 3.1kg (with BSL36B18)*3	
Standard Accessories*4	2 Batteries (BSL36A18), Charger (UC18YSL3), Driver Bit, Side Handle, Hook, Battery Cover, Carrying Case		2 Batteries (BSL36A18 / BSL1850MA / BSL1840M), Charger (UC18YSL3 / UC18YFSL), Driver Bit, Side Handle, Hook, Battery Cover, Carrying Case	

\*1. With the BSL36A18 battery.

\*2. Weight according to EPTA-Procedure 01/2014.

\*3. Sold separately.

\*4. Standard accessories vary by country or area.