

HIKOKI

Cordless Impact Driver

18V WH 18DC



BRUSHLESS
TRIPLE
HAMMER
IP56

NEW

Cordless Impact Driver

18V WH 18DE



BRUSHLESS

NEW

Specifications

Model		WH 18DC	WH 18DE
Capacity	Small Screw	4 - 10mm	4 - 8mm
	Ordinary Bolt	5 - 18mm	5 - 16mm
	High Tension Bolt	5 - 14mm	5 - 12mm
	Self Drilling Screw	Φ3.5 - Φ6mm	-
Drive		6.35mm	
Max. Tightening Torque*1		210Nm	175Nm
Battery Voltage		18V	
No Load Speed	Soft Mode	0 - 900/min	0 - 3,100/min
	Power Mode	0 - 3,400/min	
	Bolt Mode	0 - 2,900/min	
	Bolt Single Mode	0 - 2,900/min	
Impact Rate	Self Drilling Screw Mode	0 - 3,700/min	0 - 3,400/min
	Soft Mode	0 - 1,900/min	
	Power Mode	0 - 4,000/min	
	Bolt Mode	0 - 4,000/min	
Impact Rate	Bolt Single Mode	0 - 4,000/min	0 - 3,400/min
	Self Drilling Screw Mode	0 - 2,100/min	
Overall Head Length		114mm	120mm
Weight*2		1.6kg (with BSL36A18 / BSL1850MA) 1.9kg (with BSL36B18)*3	1.5kg (with BSL1840M) 1.6kg (with BSL1850MA) 1.9kg (with BSL36B18)*3
Standard Accessories*4		2 Batteries (BSL36A18 / BSL1850MA), Charger (UC18YSL3), Hook, Battery Cover, Carrying Case	2 Batteries (BSL1850MA / BSL1840M), Charger (UC18YSL3), Hook, Battery Cover, Carrying Case

*1. When tightening an M16 high-tension bolt (Grade 10.9) for three seconds with a socket adapter and a hexagon socket (40mm in overall length) attached.

*2. Weight: according to EPTA-Procedure 01/2014.

*3. Sold separately.

*4. Standard accessories vary by country or area.