

## HIKOKI

### Cordless Impact Driver

18V WH 18DC



**BRUSHLESS**  
**TRIPLE**  
**HAMMER**  
**IP56**

NEW

### Cordless Impact Driver

18V WH 18DE



**BRUSHLESS**

NEW

### Specifications

Model		WH 18DC	WH 18DE
Capacity	Small Screw	4 - 10mm	4 - 8mm
	Ordinary Bolt	5 - 18mm	5 - 16mm
	High Tension Bolt	5 - 14mm	5 - 12mm
	Self Drilling Screw	Φ3.5 - Φ6mm	-
Drive		6.35mm	
Max. Tightening Torque <sup>*1</sup>		210Nm	175Nm
Battery Voltage		18V	
No Load Speed	Soft Mode	0 - 900/min	0 - 3,100/min
	Power Mode	0 - 3,400/min	
	Bolt Mode	0 - 2,900/min	
	Bolt Single Mode	0 - 2,900/min	
Impact Rate	Self Drilling Screw Mode	0 - 3,700/min	0 - 3,400/min
	Soft Mode	0 - 1,900/min	
	Power Mode	0 - 4,000/min	
	Bolt Mode	0 - 4,000/min	
	Bolt Single Mode	0 - 4,000/min	
Overall Head Length	Self Drilling Screw Mode	0 - 2,100/min	
		114mm	120mm
Weight <sup>*2</sup>		1.6kg (with BSL36A18 / BSL1850MA)	1.5kg (with BSL1840M)
		1.9kg (with BSL36B18) <sup>*3</sup>	1.6kg (with BSL1850MA) 1.9kg (with BSL36B18) <sup>*3</sup>
Standard Accessories <sup>*4</sup>		2 Batteries (BSL36A18 / BSL1850MA), Charger (UC18YSL3), Hook, Battery Cover, Carrying Case	2 Batteries (BSL1850MA / BSL1840M), Charger (UC18YSL3), Hook, Battery Cover, Carrying Case

\*1. When tightening an M16 high-tension bolt (Grade 10.9) for three seconds with a socket adapter and a hexagon socket (40mm in overall length) attached.

\*2. Weight: according to EPTA-Procedure 01/2014.

\*3. Sold separately.

\*4. Standard accessories vary by country or area.