

Технически характеристики

HiKOKI

WR36DF(H4Z) 36V Brushless High Torque 19mm (3/4") Impact Wrench

Barcode 4966376407606

2,400Nm Nut busting torque

4 Mode tightening selector with autostop function

Reverse rotation auto-slow System

IP56 Dust and Water Resistant

Compatible with the HiKOKI MultiVolt battery



Specifications	
Voltage	36V
Motor type	Brushless
Switch type	Variable speed trigger switch with forward/reverse changeover lever
Drive	19mm (3/4") square drive
Capacity	Ordinary bolt: M12 - M36 High-tension bolt: M10 - M27
Maximum tightening torque	1,900Nm
Nut busting torque	2,400Nm
No-load speed	0 - 1,500rpm
Impact rate	0 - 2,600ipm
Autostop function	Yes
Autoslow function	Yes
IP56 Dust and Water Resistant	Yes
Light	Yes - White LED
Weight including battery	3.9kg
Length	221mm
Battery	Compatible with HiKOKI Multi Volt batteries
Included accessories	Hook

Features

2,400Nm Nut busting torque

4 mode tightening selector with auto-stop function to prevent over-tightening of bolts

Reverse rotation auto-slow function to suppress the dropping of nuts

IP56 Dust and Water Resistant

Compatible with the HiKOKI MultiVolt battery

Selling Points

2,400Nm Nut busting torque

4 Mode tightening selector with autostop function

Reverse rotation auto-slow System

IP56 Dust and Water Resistant

Compatible with the HiKOKI MultiVolt battery

Applications

Tightening and loosening of all types of bolts and nuts, used for securing structural items.