

## HIKOKI

### 18V Cordless Disc Grinders *BRUSHLESS*

#### Slide Switch



Wheel Dia.	115mm
Variable Speed	No
Brake	Yes



Wheel Dia.	125mm
Variable Speed	Yes
Brake	Yes



Wheel Dia.	125mm
Variable Speed	No
Brake	Yes

#### Paddle Switch



Wheel Dia.	125mm
Variable Speed	Yes
Brake	Yes



Wheel Dia.	125mm
Variable Speed	No
Brake	Yes

#### Slide Switch



Wheel Dia.	115mm
Variable Speed	No
Brake	No



Wheel Dia.	125mm
Variable Speed	No
Brake	No

#### Specifications

Model	G 1812DE	G 1813DVE	G 1813DE	G 1813DVF	G 1813DF	G 1812DA	G 1813DA
Kickback Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Restart Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Soft Start	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Variable Speed	No	Yes	No	Yes	No	No	No
Brake	Yes	Yes	Yes	Yes	Yes	No	No
Slide Switch	Yes	Yes	Yes	No	No	Yes	Yes
Paddle Switch	No	No	No	Yes	Yes	No	No

Switch Type	Slide Switch				Paddle Switch		Slide Switch		
Capacity	Wheel Dia.	115mm	125mm		115mm		125mm		
	Hole Dia.	22.23mm				22.23mm			
	Thickness	6mm				6mm			
Spindle Thread	M14 x 2				M14 x 2				
Battery Voltage	18V				18V				
No Load Speed	AUTO Mode	5,500/min				-			
	Transmission Mode	8,000/min	3,200 - 8,000/min	8,000/min	3,200 - 8,000/min	8,000/min	8,000/min		
Overall Length	389mm				358mm				
Weight*1	3.0kg (with BSL1850MA)	3.0kg (with BSL1850MA)		3.0kg (with BSL1850MA)		2.7kg (with BSL1850MA)		3.1kg (with BSL36B18)*2	
	3.3kg (with BSL36B18)*2	3.4kg (with BSL36B18)*2		3.4kg (with BSL36B18)*2		3.1kg (with BSL36B18)*2			
Standard Accessories*3	2 Batteries (BSL1850MA), Charger (UC18YSL3), Side Handle, Wheel Guard, Cutting Guard Clip, Wrench, 2 Battery Covers, Carrying Case				2 Batteries (BSL1850MA), Charger (UC18YSL3), Side Handle, Wheel Guard, Wrench, 2 Battery Covers, Carrying Case				

\*1. Weight according to EPTA-Procedure 01/2014.

\*2. Sold separately.

\*3. Standard accessories vary by country or area.