

HIKOKI

Wide-Area and Spot Lighting

Wide-Area Lighting with Three Light Heads Facing Different Directions



Spot Lighting with Three Light Heads Facing the Same Direction



Three Independently Pivoting LED Light Heads

Horizontally
230°



Vertically
215°



Left and Right
Heads Pivot
120°



Telescopic Head Height

Up to
2,150mm

Height
Adjustable as
Desired



4 Brightness Settings

18V		
Mode	Brightness (Luminous flux / Illuminance*)	Continuous Runtime per Charge**
Max	4,000lm / 1,650lx	Approx. 2.5h
High	3,000lm / 1,300lx	Approx. 3.5h
Mid	2,000lm / 850lx	Approx. 5.5h
Low	1,000lm / 430lx	Approx. 10.5h

Foldable Compact Design



The tripod can be made short and compact for easy storage or transport. Holding the lever and sliding it opens and closes the legs.

Cordless Tripod Light

18V UB 18DG

AC Adapter
Included as Standard

IP55 Dust and
Water Resistant**
(With a battery attached)



Specifications

Model		UB 18DG
Battery Voltage		18V
Brightness Adjustment Range	Max	4,000lm
	High	3,000lm
	Medium	2,000lm
	Low	1,000lm
LED (White)		66pcs.
Dimensions (H x L x W)	Extended	2,150 x 630 x 720mm
	Retracted	1,035 x 222 x 210mm
Weight		8.1 kg (without Battery and AC Adapter)
Standard Accessories**		AC Adapter

*1. Values measured 1m apart from the light.

*2. Using the BSL36A18. Actual runtimes may vary according to types of batteries and operating conditions.

*3. IP55 dust and water resistant products are designed to withstand the effects of dust and water, but there is no guarantee that they will not malfunction. Do not use or leave them in locations where they are subjected to excessive amounts of dusts, submerged in water, or subjected to rainwater. (Only main units conform to their protection class rating when equipped with batteries.)

*4. AC adapter is not provided for Korea, Taiwan, Malaysia, Israel, and China.