

*Photo shown with 18 V and 4.0 Ah slide Lithium-ion battery BSL1840

Drill Chuck 1.5 - 13mm (1/16 - 1/2") Keyless

Capacity: Brickl 16mm (5/8")
Capacity: Mild Steel 13mm (1/2")
Capacity: Soft Wood 65mm (2-9/16")

Capacity: Wood Screw (D x L) 8 x 100mm (#20 x 4"

Capacity: Machine

Screw 6mm (1/4

Battery Voltage 18V

No Load Speed:High 0 - 1,800/min. No Load Speed:Low 0 - 400/min. Impact Rate:High 0 - 27,000/min. Impact Rate:Low 0 - 6,000/min.

Max Torque Hard 92Nm (814in.-lbs.) Max Torque Soft 43Nm (381in.-lbs.)

Torque Setting 2 - 8Nm (18 - 71in.-lbs.)

Overall Length 242mm (9-7/32")
Weight 2.2kg (4.8lbs.)

Standard Accessories 2 Batteries (BSL1840 or BSL1830), Charger (UC18YRSL or Standard Accessories 4 UC18YR # 2*2), Side Health Poisson Bit Better Communication of the Communicati

UC18YML2*2), Side Handle, Driver Bit, Battery Cover, Carrying Case