

# UB18DAL

## 14.4V and 18V Torchlight



- Features
- For 14.4V and 18V slide batteries, BSL1430 and BSL1830
- Head angle adjustable
- Battery and charger sold separately

### Charging Time for Compatible Batteries

Battery		Charger				
Voltage	Type	Capacity* <sup>1</sup>	Cooling Windows	UC18YGSL UC18YKSL	UC18YRSL* <sup>2</sup> UC18YFSL* <sup>2</sup>	UC18YML2* <sup>2</sup> (AC/DC)* <sup>3</sup>
14.4V	BSL1415	1.5Ah	●	40min.	22min.	22/60min
	BSL1415X	1.5Ah	●	40min.	22min.	22/60min
	BSL1420	2.0Ah	●	60min.	30min.	30/80min
	BSL1425	2.5Ah	●	75min.	35min.	35/100min
	BSL1430	3.0Ah	●	90min.	45min.	45/120min
	BSL1440	4.0Ah	●	120min.	60min.	60/160min
	BSL1450	5.0Ah	●	150min.	75min.	75/200min
	BSL1815	1.5Ah	●	40min.	22min.	22/60min
18V	BSL1815X	1.5Ah	●	40min.	22min.	22/60min
	BSL1820	2.0Ah	●	60min.	30min.	30/80min
	BSL1825	2.5Ah	●	75min.	35min.	35/100min
	BSL1830	3.0Ah	●	90min.	45min.	45/120min
	BSL1840	4.0Ah	●	120min.	60min.	60/160min
	BSL1850	5.0Ah	●	150min.	75min.	75/200min