



MULTI VOLT(36V) Cordless Impact Wrenches WR36DB

Nut-Busting Torque*2

WR36DA: 1,800Nm

WR36DB: 1,650Nm

Runtime per Charge*2 (With the BSL36A18 battery)

When tightening M24 x 80 high-tension bolts (3 sec. per bolt)

WR36DA: Approx. 95 high-tension bolts

WR36DB: Approx. 100 high-tension bolts

Specifications

	Model	WR36DA	WR36DB
Capacity	Bolt	M12 – M30 (15/32" – 1-3/16")	
	High Tension Bolt	M10 – M24 (3/8" – 15/16")	
	Square Drive	19mm (3/4")	12.7mm (1/2")
	Tightening Torque	1,100Nm (812ft-lbs.)	1,050Nm (775ft-lbs.)
	Battery Voltage	36V	
No Load Speed	High Mode	0 – 1,500/min	
	Medium Mode	0 – 1,200/min	

Model	WR36DA	WR36DB
Low 2 Mode	0 – 900/min	
Low 1 Mode	0 – 600/min	
High Mode	0 – 2,900/min	0 – 2,800/min
Medium Mode	0 – 2,300/min	
Impact Rate		
Low 2 Mode	0 – 1,800/min	
Low 1 Mode	0 – 1,200/min	
Overall Length	221mm (8-45/64")	
Weight*1(Battery included)	3.7kg (8.2lbs.)	
Vibration Total Values(triax vector sum)*2	Vibration emission value ah = 15.4m/s ² Uncertainty K = 1.5m/s ²	Vibration emission value ah = 14.8m/s ² Uncertainty K = 1.5m/s ²
Standard Accessories*3	2 Batteries (BSL36A18), Charger (UC18YSL3), Battery Cover, Carrying Case	

Ташев-Галвинг ООД
www.tashev-galvning.com