

SB 18 LTX BL Q I (602353650) Cordless Impact Drill

2x18V/5.2Ah Li-ion; Charger ASC 30-36 V (/); Plastic Carry Case

Order no. 602353650
EAN 4007430297907



Product may differ from Image



- Brushless impact drill with maximum power for demanding applications
- Metabo Quick System: quick change of bit retainer and bits, for flexible working
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Unique Metabo brushless motor for quick work progress and highest efficiency when drilling and screwdriving
- Precision Stop: electronic torque control with increased precision for precise, delicate working
- High-performance impact mechanism for optimum drilling performance
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Collar (Ø 43 mm) for versatile use
- Integrated working light to illuminate the contact area
- Robust die cast aluminium gear housing for optimum heat dissipation and long service life
- With handy belt hook and bit case which can be fixed either on the right or left side
- Battery packs with capacity display for checking the charge status
- Ultra-M technology for highest performance, gentle efficient charging, optimum energy utilisation and long service life

Technical data

Characteristics

Type of battery pack	Li-ion
Battery pack voltage	18 V
Capacity of battery pack	5.2 Ah
Maximum torque - soft	60 Nm / 531 in-lbs
Pulse torque	60 Nm / 48 ft. lbs
Maximum torque, hard	120 Nm / 1062 in-lbs
Adjustable torque	1 - 20 Nm // 9 - 177 in-lbs
Drill-Ø masonry	16 mm / 5/8 "
Drill-Ø concrete	16 mm / 5/8 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	65 mm / 2 1/2 "
No-load speed	0 - 600 / 0 - 2050 /min
Maximum impact rate	32300 /min
Chuck capacity	1.5 - 13 mm // 1/16 - 1/2 "
Weight (including battery pack)	2.4 kg / 5.3 lbs kg

Vibration

Drilling in metal	3.2 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Impact drilling concrete	20.7 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	92 dB(A)
Sound power level (LwA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Quick-change chuck
 Belt hook and bit case
 2 Li-Power battery packs (18 V/5.2 Ah)
 Charger ASC 30-36 V "AIR COOLED"
 Plastic carry case
 Quick-change bit holder
 Side handle