

KHA 18 LTX (600210890) Cordless Hammer

18V ; Cardboard box

Order no. 600210890

EAN 4007430261595



Product may differ from Image



- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Variospeed (V) Electronics for working at customised speeds to suit various application materials
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- LED work light for optimum view of the drilling site
- Battery packs with capacity display for checking the charge status
- Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.

Technical data

Characteristics

| | |
|-------------------------------------|---------------------|
| Battery voltage | 18 V |
| Max. single blow energy (EPTA) | 2.2 J |
| Maximum impact rate | 4000 bpm |
| Drill-Ø concrete with hammer drills | 24 mm / 1 " |
| Drill-Ø masonry with core bits | 68 mm / 2 5/8 " |
| Drill Ø steel | 13 mm / 1/2 " |
| Drill-Ø soft wood | 25 mm / 1 " |
| No-load speed | 0 - 1100 rpm |
| Bit retainer | SDS-plus |
| Weight (including battery pack) | 2.9 kg / 6.4 lbs kg |

Vibration

| | |
|------------------------------|-----------------------|
| Hammer drilling concrete | 15 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Chiseling | 13.7 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|----------|
| Sound pressure level | 87 dB(A) |
| Sound power level (LWA) | 98 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Hammer chuck for tools with SDS-plus shank end
Carrying strap
MetaLoc case insert
rubber-coated side handle
Drilling depth guide

Ташев-Галвинг ООД
www.tashev-galving.com