Технически характеристики

HiKOKI

WR36DF(H4Z)
36V Brushless High Torque 19mm (3/4") Impact Wrench

Barcode 4966376407606

- 2,400Nm Nut busting torque
- 4 Mode tightening selector with autostop function
- Reverse rotation auto-slow System
- IP56 Dust and Water Resistant
- Compatible with the HiKOKI MultiVolt battery



MULTI VOLT

BRUSH LESS Brushless Motor

Specifications	
Voltage	36V
Motor type	Brushless
Switch type	Variable speed trigger switch with forward/reverse changeover lever
Drive	19mm (3/4") square drive
Capacity	Ordinary bolt: M12 - M36 High-tension bolt: M10 - M27
Maximum tightening torque	1,900Nm
Nut busting torque	2,400Nm
No-load speed	0 - 1,500rpm
Impact rate	0 - 2,600ipm
Autostop function	Yes
Autoslow function	Yes
IP56 Dust and Water Resistant	Yes
Light	Yes - White LED
Weight including battery	3.9kg
Length	221mm
Battery	Compatible with HiKOKI Multi Volt batteries
Included accessories	Hook

Features
2,400Nm Nut busting torque
4 mode tightening selector with auto-stop function to prevent over-tightening of bolts
Reverse rotation auto-slow function to suppress the dropping of nuts
IP56 Dust and Water Resistant
Compatible with the HiKOKI MultiVolt battery

Selling Points
2,400Nm Nut busting torque
4 Mode tightening selector with autostop function
Reverse rotation auto-slow System
IP56 Dust and Water Resistant
Compatible with the HiKOKI MultiVolt battery

Applications
Tightening and loosening of all types of bolts and nuts, used for securing structural items.

Ташев-Галвинг ООД
www.tashev-galving.com