Технически характеристики

HiKOKI

18V Cordless Disc Grinders BRUSHLESS

Slide Switch

G 1812DE



Wheel Dia.	115mm
Variable Speed	No
Brake	Yes

G 1813DVE



Wheel Dia.	125mm
Variable Speed	Yes
Brake	Yes

G 1813DE



Wheel Dia.	125mm
Variable Speed	No
Brake	Yes

Paddle Switch

G 1813DVF



Wheel Dia.	125mm
Variable Speed	Yes
Brake	Yes

G 1813DF



Wheel Dia.	125mm
Variable Speed	No
Brake	Yes

Slide Switch

G 1812DA



Wheel Dia.	115mm
Variable Speed	No
Brake	No

G 1813DA



Wheel Dia.	125mm
Variable Speed	No
Brake	No

Specifications

Model	G 1812DE	G 1813DVE	G 1813DE	G 1813DVF	G 1813DF	G 1812DA	G 1813DA
Kickback Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Restart Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Soft Start	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Variable Speed	No	Yes	No	Yes	No	No	No
Brake	Yes	Yes	Yes	Yes	Yes	No	No
Slide Switch	Yes	Yes	Yes	No	No	Yes	Yes
Paddle Switch	No	No	No	Yes	Yes	No	No

Switch Type		Slide Switch			Paddle Switch		Slide Switch	
Capacity	Wheel Dia.	115mm	125mm				115mm	125mm
	Hole Dia.	22.23mm					22.23mm	
	Thickness	6mm					6mm	
Spindle Thread		M14 x 2					M14 x 2	
Battery Voltage		18V					18V	
No Load Speed	AUTO Mode	5,500/min					-	
	Transmission Mode	8,000/min	3,200 - 8,000/min	8,000/min	3,200 - 8,000/min	8,000/min	8,000/min	
Overall Length		389mm					358mm	
Weight*1		3.0kg (with BSL1850MA) 3.3kg (with BSL36B18)*2	3.0kg (with BSL1850MA) 3.4kg (with BSL36B18)*2				2.7kg (with BSL1850MA) 3.1kg (with BSL36B18)*2	
Standard Accessories*3		2 Batteries (BSL1850MA), Charger (UC18YSL3), Side Handle, Wheel Guard, Cutting Guard Clip, Wrench, 2 Battery Covers, Carrying Case					2 Batteries (BSL1850MA), Charger (UC18YSL3), Side Handle, Wheel Guard, Wrench, 2 Battery Covers, Carrying Case	

*1. Weight according to EPTA-Procedure 01/2014.
*2. Sold separately.
0*3. Standard accessories vary by country or area.

Ташев Галвинг ООД
www.tashev.galving.com