

# Rechargeable Impact Driver



## DTW1005Z

|                                      |                                                |
|--------------------------------------|------------------------------------------------|
| Напрежение:                          | 18 V LXT                                       |
| Капацитет на батерията:              | 1,5 / 2,0 / 3,0 / 4,0 / 5,0 / 6,0Ah            |
| Вид на батерията:                    | Li-ion                                         |
| Удари в минута:                      | 0 - 1.600min <sup>-1</sup>                     |
| Удари в минута / ниски:              | 0 - 1.800min <sup>-1</sup>                     |
| Удари в минута / високи:             | 0 - 2.200min <sup>-1</sup>                     |
| Обороти на празен ход - 1./2./3./4.: | 0 - 800 / 900 / 1.000 / 1.800min <sup>-1</sup> |
| Удари в минута - 1./2./3./4.:        | 0 - 1.600 / 1.800 / 2.200min <sup>-1</sup>     |
| Стандартни болтове:                  | M12 - M33                                      |
| Високоякостни болтове:               | M10 - M24                                      |
| Square drive:                        | 3/4"                                           |
| Въртящ момент - висок:               | 1360Nm                                         |
| Nut-busting torque:                  | 1.700Nm                                        |
| Шум: звуково налягане:               | 100,0dB(A)                                     |
| Шум: звукова мощност:                | 108,0dB(A)                                     |
| Шум: отклонение:                     | 3,0dB(A)                                       |
| Вибрации: затягане с удар:           | 14,2m/s <sup>2</sup>                           |
| Размери (Д x Ш x В):                 | 339 x 91 x 291mm                               |
| Тегло:                               | 4,2kg                                          |



- Twin LED work light with pre-glow and after-glow functions.
- Variable speed trigger and full-speed mode which, when activated, allows full speed to be reached with less trigger pull, reducing hand fatigue.
- Automatic stop mode available in forward operation (3 stages) and reverse (1 stage).
- Provides stable torque until the end of battery capacity and control for constant speed.