

Driver Drill LXT®, 18V, 141 Nm, 0 – 2 100 min⁻¹

DDF492Z

18V, 141 Nm, 0 – 2 100 min⁻¹

Model DDF492 is a drill driver powered by an 18V LXT Li-ion battery.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
No load speed	0 - 550 / 0 - 2100 min ⁻¹
Max. fastening torque Hard/Soft	130 / 65 Nm
Torque setting	21
Max Torque	141 Nm
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	76 mm
Drilling Capacity Wood (Auger Bit)	50 mm
Drilling Capacity Wood (Self-feed bit)	76 mm
Drilling Capacity Hole Saw	152 mm
Drill Chuck Capacity	1,5 - 13 mm
Sound Power Level (L _{WA})	88 dB(A)
Sound Pressure Level (L _{pA})	80 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Tool weight with battery	2,3 - 2,6 kg

User benefits

- Highly efficient and compact machine for professional use
- Keyless chuck for easy bit installation and removal
- LED light illuminates the work site
- Electronic overload protection protects the user and the device
- Battery protection system automatically shuts off power when the battery level is low
- Compact and lightweight for reduced operator fatigue
- Electric brake for maximum productivity and increased operator safety

EAN 0197050011701

Link to product - www.makitauk.com



Related products

Standard AC

251314-2 (2x)

Truss Head Screw M4*12, Td140D

452947-8

Bitholder



346317-0
Belt Hook



784637-8
Screw Bit, Ph2 – S6, 45 Mm, Double



Optional AC

251314-2 (2x)

Truss Head Screw M4*12, Td140D

346449-3

Belt Hook

784637-8

Screw Bit, Ph2 – S6, 45 Mm, Double

837916-4

MakPac (2) Inlay



346317-0
Belt Hook



452947-8
Bitholder



821550-0
Makpac case (2)



D-72833
Metal Drill Bit set HSS-Tin, 2 - 8 mm,



Other

User manual

Parts drawing