

Полирпаста Bellinzoni за мрамор и гранит 0.750 л



Description:

Product in a paste form for polishing any kind of stone. Its special chemical composition allows it to dry quickly in order to proceed quickly with others jobs to be made on the stone. The results of this treatment is a brilliant shine that lasts for long time. It is studied to "cover" variation of colors of the material and imperfections due to the previous polishing. Special Preparation is also suggested when is necessary to renew the original polishing of old material that has lost the original shine. The range is available in different colors in order to polish and enhance colors of different kind of materials.

Technical Characteristics:

Appearance	Paste
Colour availables	Colourless (neutral whitish) Black Red Brown Yellow Green
Odor	Characteristic of solvent
Specific gravity at 20°C	1,40 ± 0,02
Hydro-solubility	Insoluble
PH	n.a.
Shelf life at 20° C (68° F)	12 months in original packing

Instruction for Use:

Surface must be clean and dry; stains, mildew, crusting must be scraped off and free of powder. Apply a spoon of product on the surface to polish, distribute homogenously using a clean cloth or using a tool for application of creamy products. Let it dry for approx. 10 minutes. Proceed to polish. For manual polish is suggested to use fine steel wool (000) without soap; for fast polishing use an electrical flex machine at low speed (max. 2.000 rpm) equipped with felt disc or cloth. In case of floor application is possible to polish by using a single disc polishing machine with steel wool or floor polishing machine with polishing pad.

Suggestion for Use:

To facilitate penetration of the preparation is suggested to warm the slab to be treated in order to open porosities and to facilitate the penetration of the polisher deeply into the slab.
The longer the preparation remains on the surface the better will be the final result.

- To delay drying time of the polisher we suggest to dilute the preparation with turpentine-based solvent by

In case of floor application pay attention that the floor could become slippery; the slipperiness will decrease after some days because of the subsequent cleaning and washing of the floor; also after maintenance the floor will maintain an excellent shine.

We suggest not to apply the preparation on synthetic materials as plastic, rubber, linoleum etc...

- Before use, read carefully recommendations printed on the tin.

Application on surfaces:

Marble, granite, travertine, slate, tiles, terrazzo, agglomerates and engineered stones.

Safety procedures:

As far as the proper working procedures is concerned, we recommend to consult Material Safety Data Sheets issued according to E.U. rules and to follow your national laws concerning safety in the working place.

Coverage:

For polishing of marble and granite polished or grinded above grit 800, with 1 kg (35 oz.) of product is possible to treat 40/50 sqm (430/500 sq.ft.) In case of calcareous stone, limestone, sand stone, concrete polished or grinded above grit 800 with 1 kg (35 oz.) of product, it is possible to treat 20/30 sqm (200/300 sq.ft.).

Packing:

Carton: 15 tins of 1,300 kg (45 oz), 3 tins of 6 kg (13 lb) , 1 drum of 20 kg (44 lb)

The composition of the tins is Steel (ACC). After use, comply with the local and national regulations currently in force regarding recycling.

Our packing is conformed as per U.N. rules for inland transport (A.D.R.) and by sea (I.M.O.) for transportation via air refer to updated rules (I.A.T.A.). For further information regarding transport please check MSDS.

Harmonized Custom Tariff:

34.04.9090

Продукт: [Полирпаста Bellinzoni за мрамор и гранит 0.750 л](#)

Категория: [Консумативи за шлайфмашини](#)

Бранд: [Bellinzoni](#)

Категория бранд: [Полирпаста Bellinzoni](#)