

Боя Motip Dupli спрей за джанти 0.6 л, мишосива, RAL 7005, Color Car's

Quality and properties

- High-grade nitro-combi quality
- Very good coverage
- Excellent adhesion
- Good flow, smooth surface
- Quick-drying
- Suitable for indoors and outdoors applications
- Weather-resistant, light-proof, UV-resistant
- Scratch-, shock- and impact-resistant
- High surface hardness and good elasticiy
- Polishable, dirt-resistand surface

Physical and chemical data

- Basis of the binder: nitro-combi
- **Colour:** black or white, glossy, satin mat or matt
- **Smell:** solvent
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530):
 - glossy: 80-85 gloss units
 - satin matt: 30-40 gloss units matt: 10-
- 20 gloss units
- Efficiency:
 - Depending on consistence and color of the ground: 400 ml are sufficient for approx. 1.3 m² 600 ml are sufficient for approx. 2.0 m²
- Drying time (at 20°C, 50% relative air humidity): Dust-dry: after approx. 10 minutes Dry to touch: after approx. 50 minutes Cured: after approx. 24 hours

The drying time depends on surrounding temperature, air humidity and thickness of the applied

coat.

- **Temperature-resistant:** up to 80°C
- Storage stability:
 - 10 years, if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:** aerosol cans, maximum nominal volume 400 ml resp. 600 ml

Environment and labelling

Environmentally sound: The products of MOTIP DUPLI are 100% free of heavy metals. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products made by MOTIP DUPLI comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

Using instructions

The most DUPLI-COLOR spray paints have a so-called no-spray ring or a tamper-proof cap. This is to avoid unauthorized use. Please see the corresponding advises on the cap or on the label. **Before use, carefully read and observe the warning texts on the label! Application**

Preparation of the ground:

- Clean underground from dirt, fat and rust.
- Fill and sand uneven surfaces.
- If no filling with putty is necessary, apply a primer, e.g. CAR's Primer.
- Otherwise apply DUPLI-COLOR Filler on the fine-sanded filled surfaces. Before that, generously mask off the repair spot.
 - If bigger areas have to be repaired, we recommend to mask off edges of the car body.

Lacquering:

- The surface has to be clean, dry and free from fat.
- Mask off areas not to be painted.
- Before use, shake the can vigorously for 3 minutes.
- Test spray to check colour-matching.
- The spray distance should be approx. 20-30 cm.
- Spray several thin cross-coats in 3 5 minute intervals.
- Do not spray over synthetic paints!

Tips for spray painting

Protect the object and the surrounding area from spray mist. When painting small areas it is recommended that a piece of card is used as a mask, with a hole cut in it slightly larger than the area to be sprayed. The mask should be held 1 to 2 cm from the surface. With this method, the mainly part of the spray mist is brought under control. It recommends to mask parts not to be lacquered, to protect the surrounding against the spray mist.

The aerosol can should have room temperature.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Продукт: <u>Боя Motip Dupli спрей за джанти 0.6 л, мишосива, RAL 7005, Color Car's</u> Категория: <u>Аерозолни покрития - спрейове</u> Бранд: <u>Motip Dupli</u> Категория бранд: Боя Motip Dupli