



Nautical White Lithium Grease (G003)

Lubricant spray specific for the nautical sector, perfect for situations with high a presence of salt and aggressive corrosive atmospheres. The product operates in both high and low temperature.



Quantity	400 ml
Barcode	EAN13: 8034108890029
Box / Case	12 pz

NAUTICAL LITHIUM GREASE – This grease contains lithium and titanium oxides that make it specific and particularly suitable for the nautical sector. It has excellent long-term lubrication and performs in the presence of saline and aggressive atmospheres. It has long-term stability and resistance to oxidation. It protects surfaces from corrosive agents and it's perfectly suitable for both high temperatures (220°C/428°F) and low temperatures (-40°C/-40°F). Excellent for lubricating pins, joints, transmissions, levers, suspensions, hinges and exposed machine parts on outboard motors and boats.

Technical Specifications:

Aspect	Tin-Plate can containing under pressure fluid
Color	Whitish
Odour	Characteristic of solvent
Relative density	at 20°C 0,63 ÷ 0,67 g/ml
Flash point	Und .0° C extremely flammable
Pressure at 20°C	4/6 bar
Consistency	NLGI EP2
Penetration	265 - 295 at 25°C 0.1 mm
Drip point	+ 190 °C
Application temperature	- 40°C - + 220°C

HOW TO USE: shake and spray directly on the surface from a distance of 15-25 cm. The product could be also be used with a straw that is attached to the cap.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT