



Molybdenum bisulfide Grease, MOS2 (G005)

The molybdenum bisulfide grease is a chemical mixture that creates a glossy mineral, it is soft and oily, perfect for lubrication. This product is an efficient lubricant of Ambro-Sol, stable and anti-oxidizing.



HOW TO USE: shake and spray directly on the surface from a distance of 15-25 cm. The product could be also be used with a straw that is attached to the cap.

Quantity	400 ml
Barcode	EAN 13: 8034108890043
Box / Case	12 pz

MOLYBDENUM BISULFIDE GREASE – This superior classic black grease stands out because of its adhesiveness to metals in the most difficult conditions. It is high temperature resistant (300°C/572°F). It features extraordinary mechanical stability and provides excellent protection against oxidation, humidity and corrosion. It is ideal for lubricating both standard and high-load bearings.

Technical Specifications:

Aspect	Tin-plate can containing under pressure fluid
Color	Black
Odour	Typical of solvent
Relative density	at 20°C 0,69 ÷ 0,73 g/ml
Flash point	Und. 0° C extremely flammable
Pressure at 20°C	4/6 bar
Consistence	NLGI EP 2
Wheel Bearing test	(3 hour at 80°C) < 10 %
Drip point	> 270°C
Penetration at 25°	265 - 295 mm/10
Application temperature	-20°C - 300°C (peak)

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT