



## Copper Grease 400 ml (G006)

This grease has special anti-corrosive properties; it's a perfect lubricant for situations where high temperature is present: it resists until 1000°C, and it prevents episodes of blocking.



Quantity	400 ml
Barcode	EAN 13: 8034108890050
Box / Case	12 pz

**COPPER GREASE** – This product is made of super fine foliated copper particles and special corrosion inhibitors. It has protective and lubricating properties at high temperatures. High temperature resistance to 1000 °C/1832°F. High adhesive capacity and anti-corrosion capacity make it ideal for all cases where heat or a highly corrosive environment can create irreversible blocks: slip, ring, pins, motor, exhausts, electrical, contacts, threaded connections, injection valves, etc.

### Technical Specifications:

Aspect	Tin-Plate can containing under pressure fluid
Color	Light brown/Orange
Odour	Characteristic of solvent
Relative density	at 20°C 0,64 ÷ 0,68 g/ml
Flash point	Und. 0° C extremely flammable
Pressure at 20°C	4/6 bar
Consistence	NLGI EP 2
Penetration at 25°	265 - 295 mm/10
Drip point	ASTM D566 infusibile
Application temperature	-40 °C - 1000°C/1100 °C (peak)

**HOW TO USE:** shake and spray directly on the surface from a distance of 15-25 cm. The product could be also be used with a straw that is attached to the cap.

### MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

**BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT**