



Marker Paint 360° (V403)

This product can be used in all position thanks to its special 360° valve. This spray is ideal for professional uses on surfaces such as asphalts and walls, but also for domestic use on woods and floors. It's available in different colors.

360° MARKER PAINT - A spray paint for marking masonry, pavements, asphalt, cement and wood. It is resistant to weathering and wear. It is available in fluorescent colors. The product comes with a special "360° valve," so it can be used in any position.



FIELDS OF APPLICATION:

Surfaces in wood, surfaces in metal, glass, plastic, concrete and asphalt.

Technical specifications:

Quantity	500 ml
Box / Case	12 Pz.
Aspect	Tin-Plate can containing under pressure fluid
Chemical nature	Paint Synthetic resin based
Color	fluo-pastel
Odour	Characteristic of solvent
Relative density	At 20°C 0,82÷ 0,86 g/ml
Writings on the bottom	Barcode, date of production, name of product
Flash point	Und. 0° C extremely flammable
Pressure	at 20°C 5,5 ± 0,5 bar
Pressure	At 50°C 8,0 ± 0,5 bar
Viscosity Ford Cup	From 28" to 33"
Dry residual in the can	From 30 to 35 %
Overcoating	Yes
Brilliance	From 0 to 15 Gloss (60 ° angle gloss meter)
Operating temperature	-10°C / +100°C (Picchi 150° C)
Drying times at 20°C	Out dust: 10 minutes
	Dry to touch: 10 minutes
	Dry in full depth: 45 minutes
Color reference ring	
The product is permanent and resistant to UV rays and humidity.	

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 5°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 36 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT