



Plastic primer HQ (V400PRIMER2)

PLASTIC PRIMER HQ - It's the high quality primer to be applied before painting, it provides a perfect adhesion for all surfaces such as plastic, ABS, methacrylate, rigid PVC, polypropylene and polycarbonate.



Technical Specifications:

Quantity	400 ml
Box / Case	6 Pz.
Aspect	Tin-Plate can containing under pressure fluid
Chemical nature	Synthetic
Colour	Trasparent
Odour	Characteristic of solvent
Relative density at 20°C	0,76 ÷ 0,78 g/ml
Flash point	Und. 0° C extremely flammable
Writing on spray bottom	Barcode, Batch date, product name
Pressure	at 20°C 5,5 ± 0,5 bar
Pressure	at 50°C 8,0 ± 0,5 bar
Dry residual in spray	1%
Gloss	80 Gloss (Glossmeter angle 60°)
Resistance temperature	-10°C / 80°C
Drying time T=20°C:	Out dust: 15-30 minutes Dry to touch: 15-30 minutes Dry in full depth: 22 hours Overcoating Interval: 22/48 hours
Security cap child-proof patented and registered	

Product subject to directive C.O.V.
Subcategory: Special finishes
Limit value COV: 840 g/Liter

FIELDS OF APPLICATION: plastic, ABS, methacrylate, rigid PVC, polypropylene and polycarbonate. Apply at room temperature: Min 5°C – Max 35°C.

INSTRUCTIONS FOR USE:

- Vigorously shake the can for at least 1 minute, until you hear the inner marbles move freely. It is also suggested to occasionally shake the cylinder even during use;
- Carefully clean the surface before application;
- Test in a hidden area to verify compatibility of the surface with the paint.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 5°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT