



Dark Zinc 400 ml (Z351)

This product dries rapidly, it can be left as final protective coat or it can be primer and painted on top. It protects from impurity and atmospheric agents. It adjusts, redefines, repairs.

DARK ZINC – This organic galvanizer has a synthetic resin base containing a high quantity of pure micronized zinc and aluminium. The high zinc content provides the product with an excellent corrosion resistance. The product can be used either as a finish or can be painted over. It dries rapidly, permitting the surface treated to be used after just 8-10 minutes. Ideal for retouching, finishing, and repairing all galvanized parts.



Technical Specifications:

Quantity	400 ml
Box / Case	12 pcs
Barcode	EAN 13 8034108890357
Aspect	Tin-Plate can containing under pressure fluid
Physical state	Pigmented liquid in aerosol
Flash point	Und. 0° C extremely flammable
Pressure	at 20°C 5,5 bar
Relative density	at 20°C 0,78 ÷ 0,81 g/ml
Propellant	LPG
Chemical nature	Synthetic resin with inhibiting pigment of corrosion based of zinc dust
Colour	dark grey
Powder purity Zn	> 98%
Odour	Characteristic of solvent
% Metal in the dry film	87 %
% Zinc in the dry film	59 %
Resistance temperature	300 °C (peak 400 °C)
Coverage	2/3 mq2
Drying times = 20°	Out dust: 10' Dry to touch: 20' Dry in depth: 6 ore Overpainted after 12 hours

APPLICATION FIELDS: Surfaces in metal as iron, aluminum, steel. Protection of ferrous metallic structures, pipelines, eaves, enclosures, job utensils etc.

HOW TO USE: Carefully clean the surface to be treated, eliminating encrustations and traces of rust with synthetic thinner. If necessary, sand with abrasive paper. Turn the can upside-down and shake well until the marbles move freely inside. To avoid dripping apply twice from a distance of about 20-30 cm. Once finished, spray for 2-3 seconds with the can upside-down to clean the valve and allow for future use.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 5°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT