

## TECHNICAL DATA SHEET

EDITION: FEBRUARY 2025

B096 | **DECO CHALK**

REPLACES ALL EARLIER VERSIONS

decorative  
coatings & primers

B

## DECO CHALK

chalk decorative paint with matte finish

- great coverage and excellent spread
- strong adhesion to difficult surfaces
- velvety matte finish

DECO CHALK is a decorative water-based paint that creates a mat finish and plenty of decorative effects, dichromate, vintage style, shabby chic. Ideal for restoration and decoration of wooden furniture, walls or objects made of various materials such as wood, glass, iron, marble, plastics, wallpaper, brick, cement etc. It is odorless. Applies directly to all painted or varnished surfaces. Where required, appropriate preparation such as sanding or priming.

	<b>COVERAGE</b> 12±2m <sup>2</sup> /L
	<b>FINISH</b> MATT
	<b>THINNING</b> 0-10% WATER
	<b>DRYING TIME</b> ½ -1 hour*
	<b>RECOATING TIME</b> 4-6 hours*
	<b>RECOMMENDED NUMBER OF COATS</b> 1-2 coats
	<b>TOOLS</b> roller, brush or airless paint sprayer

\* Lower temperatures or higher relative humidity will prolong drying and recoating times.



## TECHNICAL CHARACTERISTICS

TYPE	ACRYLIC	
SPECIFIC GRAVITY	WHITE READY-MADE SHADES BASES	1,50 ±0,10 g/cm <sup>3</sup>
<b>SOLIDS w/w</b> (ISO 3251-03)	63±2 % *	
<b>SOLIDS v/v</b> (ISO 3233-98)	47±3 % *	
<b>VISCOSITY</b> (ASTM D 562-05 @ 25°C)	KU 125±10 *	
<b>APPLICATION VISCOSITY</b> (ASTM D 562-05 @ 25°C)	KU 100±15 *	
<b>pH</b>	8.5±0.3	
<b>HIDING POWER</b> (ISO 3905)	98%   150µm wet film*	
<b>WHITENESS INDEX</b> (ASTM E 313-05)	≥ 83*	
<b>YELLOWNESS INDEX</b> (ASTM E 313-05)	≤ 3*	
<b>GLOSS (60°)</b> (ISO 2813-99)	2±1 *	
<b>GLOSS (85°)</b> (ISO 2813-99)	6±2 *	
<b>APPLICATION TEMPERATURE</b>	min 5°C -max 30°C	

\*valid only for white.

## DIRECTIVE 2004/42/CE

EU Limit value for this product in a ready-to-use condition (cat A/L: Decorative effect coatings): 200 g/L (2010). This product contains max: 199 g/L VOC.