

Грунд Berling за бои и мазилки 3 л, прозрачен, Acrylic Emulsion Primer



Description

100% acrylic water-based primer for use before applying emulsion and acrylic paints. Suitable for indoor and outdoor use.

Purpose of Use

Priming of both exterior and interior surfaces, walls and ceilings

Product Characteristics

Transparent substrate. Very good adhesion. High performance.
Low Volatile Organic Compounds content.

Shades

Available in transparent and it is not tinted

Packaging

0.75L - 3L - 10L

Application conditions

The application is carried out at an ambient temperature of 8 °C to 35 °C and a maximum relative humidity of 80%.

Surface preparation

Surfaces to be painted should be dry and clean of any dust, grease, salt and old peeled paints. Any

holes, cracks or unevenness of the wall should be puttied with Berling's Acrylic Putty or Two component Putty. The product is applied by brush or roller.

Technical characteristics

VOC: 10gr/lit (maximum VOC content ready for use). Specific gravity: 1.02 ± 0.03gr/cm³ (ISO 2811). Viscosity: 90-115 K.U., 250C (ASTM D562).

pH: 8-9

Coverage: 10 - 12m²/lit, depending on the application method.

Solvent: Water.

Thinning: Thin with water at 300% by volume.

Application: The product is applied by brush or roller.

Drying time: Touch dry from 2 to 4 hours. (These times may be prolonged depending on temperature and humidity).

Продукт: [рунд Berling за бои и мазилки 3 л, прозрачен, Acrylic Emulsion Primer](#)

Категория: [Бои на водна основа](#)

Бранд: [Berling](#)

Категория бранд: [Грунд Berling](#)

Ташев-Галвинг ООД
www.tashev-galving.com