



Technical Data Sheet

CoversUp Aerosol

Generic Type – Acrylic, solvent-based, interior stain blocking primer-sealer and finish coat.

Performance Characteristics –

- Quick cure for water stains
- Ideal for common overhead stains
- Matches the colour of most ceiling tiles
- Flat white finish won't yellow
- Low odour aerosol
- May be used as a primer or primer / finish
- Use under or over any latex or solvent-based paint

Recommended Uses–

Apply as a primer / finish to interior acoustic ceiling tiles or painted ceilings, light fixtures, HVAC ductwork and vents, overhead pipes and conduit, or anywhere an overhead high hiding stain sealing primer or spot finish is needed.

Interior Substrates–

New, primed or previously painted ceiling tiles, drywall, cured plaster, cement, stucco, wood (pine, fir, birch, oak and plywood), aluminum, iron, steel and galvanized metal, PVC, glossy laminates and other interior surfaces.

General Description –CoversUp™ Aerosol is a low odour vertical aerosol that is a stain killer and ceiling touch-up paint in one. It seals water damaged ceilings and sprays vertically for ease of use. It's perfect for touch up when you don't want to repaint the entire ceiling due to spot damage. Zinsser's stain blocking primer technology is incorporated into this new generation product that offers a flat white finish that matches most new acoustical ceiling tiles and white ceiling paints. CoversUp™ is an odourless solvent based formula with only a brief odour from propellants that diminishes quickly.

Stain Killer–

One coat will effectively block most water stains, graffiti, nicotine, and smoke stains. If a second coat is desired, allow to dry two hours before recoating.

Ceiling Paint for Ceiling Tiles–

Use to block water, nicotine or smoke stains on ceiling tiles. Dries flat and matches the colour of most ceiling tiles.

Paint or Primer for All Ceilings–

Dries flat and will match some white painted ceilings. Use as a stain blocking primer for any ceiling surface. May be top coated with ceiling paint in two hours when used as a primer.

Surface Preparation

Surfaces should be clean, dry, sound and free of dust, dirt, excessive chalky material, grime, grease, oil, wax, mildew, wallpaper adhesive or any contamination that may interfere

with adhesion. If unsure, always wash surface with a household ammonia and water solution, appropriate cleaning solution, or solvent (Do not use tri sodium phosphate based cleaners). Remove any unsoundly adhered coatings. Sand any remaining paint film edges smooth with the surface. Attempt to remove existing stains by washing, sanding, scraping, etc. Remove interior mildew with an interior mildew cleaner, such as Zinsser Mould Killer & Remover. Countersink exposed nail heads, spot-prime and fill. Wire brush rusty areas.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **Special precautions should be taken during the surface preparation of pre 1960's paint surfaces over wood and metal as they may contain harmful lead. When dry-sanding avoid dust inhalation by wearing a suitable protective face mask.**

Application Directions– Shake can until ball inside rattles, then continue shaking for one minute. Repeat shaking periodically during use. Test spray pattern on scrap surface before using. Spray 25-30cm from surface. Mask off nearby objects. Apply with short 'dusting' strokes. Will seal most stains. When finished, clean valve by holding can upside down and spraying until clear gas comes out. To clear clogged spray tip, remove from can and clean with pin.

Application conditions–

Apply within the following ranges:

Humidity: 0% to 85%

Temperature: 4oC to 32oC

Drying Time: Dries to the touch in 30 minutes. Allow a minimum of 2 hours dry time before recoating or applying topcoat. Lower temperature and higher humidity will prolong dry time of the product.

Coverage–

Approximately 1.5m² per aerosol can.

Surface porosity may reduce square foot coverage and require a second coat.

Cleanup–

Clean spills and drips with a rag dampened in mineral spirits.

Disposal–

Dispose of unused or unwanted product in accordance with local laws regulating water-based coatings.

DANGER! EXTREMELY FLAMMABLE AEROSOL!

Contains Acetone. Causes serious eye irritation. May cause drowsiness or dizziness. Read label before use. If medical advice is needed: Have product container or label

at hand. Do not spray on an open flame or other ignition source. Avoid breathing vapour or spray. Wear protective gloves and eye protection: gloves: natural rubber (latex) or nitrile rubber, safety glasses with side-shields. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations. Pressurized container: may burst if heated. Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of the reach of children. Repeated exposure may cause skin dryness or cracking

KEEP OUT OF REACH OF CHILDREN.

Limitations–

Covers UP is not intended for application to floors, decks, roof surfaces or any surface subject to immersion or prolonged contact with water.

Precautions–

Consult product Safety Data Sheet.

Warranty–

CoversUp™ is guaranteed to perform as indicated when applied according to label directions to a properly prepared surface. Directions are as complete as possible but cannot encompass all conditions, applications, and / or surfaces beyond manufacturer's control. The contents of the container are warranted to be free from any other defect for 2 years from the date of manufacture. All warranties and guarantees are limited to refund or replacement of product used with proof of purchase. No other warranty or guarantee is expressed or implied.

Specification Data–

Dry time: (touch) @ 20°C: 30 minutes

May recoat / topcoat: 2 hours

Shelf Life: 3 years

Storage / Handling: Store indoors 5 – 25°C

Freeze / thaw stable